

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date
of well completion.

STATE OF OREGON
(Please type or print)

RECEIVED

1967 27 1968

State Well No.

State Permit No.

3/1w-33

Name **Mr. Paul H. Daily**
Address **Rt. 2 Box 148 Aurora Oregon**

County Marion Driller's well number _____
No. 1 N.E. ¼ Section 33 T. 3 S. R. 1W W.M.
 Bearing and distance from section or subdivision corner _____

Well #2

Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
Abandonment, describe material and procedure in Item 12.

Domestic ☐ Industrial ☐ Municipal ☐ Rotary ☐ Driven ☐
Irrigation ☒ Test Well ☐ Other ☐ Cable ☒ Jetted ☐
Dug ☐ Bored ☐

(6) CASING INSTALLED: Threaded ☐ Welded ☒

12" Diam. from 0 ft. to 107 ft. Gage 279

10" Diam. from 93 ft. to 123 ft. Gage 250

" Diam. from ft. to ft. Gage

(7) PERFORATIONS: Perforated? ☒ Yes ☐ No

Type of perforator used **Torch (10 " only)**

Size of perforations **1/8** in. by **10** in.

175 perforations from **97** ft. to **123** ft.

perforations from ft. to ft.

perforations from ft. to ft.

perforations from ft. to ft.

perforations from ft. to ft.

(8) SCREENS: Well screen installed? ☐ Yes ☒ No

Manufacturer's Name Model No.

Diam. Slot size Set from ft. to ft.

Diam. Slot size Set from ft. to ft.

Well seal—Material used in seal Bentonite, cement & sand
Depth of seal 30 ft. Was a packer used? No
Diameter of well bore to bottom of seal 16 in.
Were any loose strata cemented off? ☐ Yes ☒ No Depth
Was a drive shoe used? ☐ Yes ☒ No
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from ft. to ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? depth of strata
Method of sealing strata off

Static level 38 ft. below land surface Date 5/17/66
Artesian pressure _____ lbs. per square inch Date _____

(11) WELL TESTS: Drawdown is amount water level is lowered below static level. **HAakon BOTTLNER CO.**
Was a pump test made? ☒ Yes ☐ No If yes, by whom?

Yield:	300	gal./min. with	45	ft. drawdown after	4	hrs
"	575	"	70	"	6	"

"	"	"	"
Baller test	gal./min. with	ft. drawdown after	hrs

Artesian flow g.p.m. Date _____

Temperature of water 53 Was a chemical analysis made? ☐ Yes ☒ No

(12) WELL LOG: Diameter of well below casing 12 " Back-filled to
Depth drilled 129 ft. Depth of completed well 123 ft. w/gravel
Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.

MATERIAL	FROM	TO
Top soil	0	2
Clay, yellow	2	40
Clay, yellow sandy	40	90
Sand, brown	90	95
Gravel & sand (water Bearing)	95	123
Clay, grey	123	129

Work started	April 25	1966	Completed	May 10	1966
Date well drilling machine moved off of well	May 11	1966			

Manufacturer's Name **Bowl assembly is Lane & Bowler**
Type: **New** H.P. **30**

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME Haakon Bottner Drilling Company
(Person, firm or corporation) (Type or print)

Address 3424 S.E. 174th. Avenue
Portland Oregon (97236)

Drilling Machine Operator's License No.246.....

[Signed] Harmon B. Butler
(Water Well Contractor)

Contractor's License No. 109 Date _____, 19____