

filed with the

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date
of well completion.

STATE OF OREGON
Please type or print

State Well No. 75 2W-32

State Permit No. 3/25/83 IOB

1808 South Beach Medford Ore 97501

(1) OWNER:

Name Phil Ginther

Address

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Cable Driven Jetted Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal Irrigation Test Well Other

CASING INSTALLED:

Threaded Welded 1/4"

8" Diam. from 1 ft. to 138 ft. Gage

" Diam. from ft. to ft. Gage

" Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? Yes No

Type of perforator used M:11

Size of perforations 1/4" in. by 2 in.

408 perforations from 80' ft. to 145' ft.

perforations from ft. to ft.

perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No

Manufacturer's Name

Type Model No.

Diam. Slot size Set from ft. to ft.

Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? Yes No If yes, by whom?

1: gal./min. with ft. drawdown after hrs.

notest at this time

Baller test gal./min. with ft. drawdown after hrs.

Artesian flow g.p.m.

Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Bentonite

Well sealed from land surface to 19' ft.

Diameter of well bore to bottom of seal 12 in.

Diameter of well bore below seal 8 in.

Number of sacks of cement used in well seal sacks

Number of sacks of bentonite used in well seal 4 sacks

Brand name of bentonite Natural brand

Number of pounds of bentonite per 100 gallons

of water lbs./100 gals.

Was a drive shoe used? Yes No Plugs Size: location ft.

Did any strata contain unusable water? Yes No

Type of water? depth of strata

Method of sealing strata off

Was well gravel packed? Yes No Size of gravel:

Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County MARION 32-Driller's well number

1/4 Section 32 T. 7S R. 2W W.M.

Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 27 ft.

Static level ft. below land surface. Date

Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 8"

Depth drilled 139 ft. Depth of completed well 139 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
brown clay	0	23	
" " sand gravel	23	27	
med gravel and sand	27	40	15
clay sandy brown	40	62	
gray clay	62	69	
gray sand and pe gravel	69	71	16
brown clay	71	73	12
clay	73	79	
gravel brown sand	79	102	13
gravel silt	102	106	
cemented gravel	106	120	25
pe gravel	120	123	30
	123	125	30
cemented gravel with layers of loose gravel	125	127	
red clay with gravel	127	130	
yellow-brown clay	130	139	

Work started 19 Completed May 20 1974

Date well drilling machine moved off of well May 20 1974

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Tom Peck Date 20, 19 74

(Drilling Machine Operator)

Drilling Machine Operator's License No. 924

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name ROBINSON'S EOLA WELL DRILLING

(Person, firm, or corporation)

(Type or print)

Address SALEM, OR

[Signed] Henry H. Robinson (Water Well Contractor)

Contractor's License No. 13 Date 5-29, 19 74