## WATER WELL REPORT STATE OF OREGON

MARILLA

## MAGGEIVED

JUL 1 4 1982

WATER RESOUL ER RESOUL TT.

State Well No.	35/1W-34-cbc
State Well No.	35/1W-34-cbc

State Permit No.

(1) OWNER:	(10) LOCATION OF WELL:			
Name CLACKAMAS GREENHOUSE, INC.	County Marion Driller's we	ll number 7	· <b>-</b> 82	
Address 23646 Klupenger Road	W1 4 SN 4 Section 34 T.3S	r.lW	W.M.	
City Aurora, Oregon 97002 State	Tax Lot # Lot Blk		ivision	
(2) TYPE OF WORK (check):	Address at well location: 23646 Klupenger			
New Well   Deepening □ Reconditioning □ Abandon □	Anrora, Oregon	<del>}</del> 7002		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed v	vell.		
	Depth at which water was first found	198	ft.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):			Date7-3-82	
Rotary Air Driven Domestic Dindustrial Municipal D		er square incl		
Rotary Mud	(12) WELL LOG: Diameter of well below casing			
CASING INSTALLED: Steel Plastic	Depth drilled 215 ft. Depth of completed well 214 ft.			
CASING INSTALLED: Steel M Plastic  Threaded  Welded M	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.			
6"Diam. from plus1ft. to193ft. Gauge •250				
5"Diam. from				
LINER INSTALLED: 215 •252	MATERIAL	From	To SWL	
"Diam. from	Clay-tan-silty	0	23	
	Clay_blue_silty	23	46	
(6) PERFORATIONS: Perforated? ☐ Yes 🏗 No Type of perforator used	Clay_gray_silty	46	71	
Size of perforations in. by in.	Sand_dirty_gray	71	83	
perforations from ft. to ft.	Clay-sticky-gray	83	95	
perforations from	Clay-tan-sandy		106	
perforations fromft. toft.	Sand-gravel-brown		113 12	
	_Sandstone=brown		127	
(7) SCREENS: Well screen installed?   Well screen installed?   Yes □ No  Manufacturer's Name UPO JOHNSON	Clay-green		139	
Type stainless Model No. 304ss	<u>Clay-gray-sandy</u>		153 161	
Diam. 6. Slot Size 50. Set from 200. ft. to 205. ft.	Sandstone-green		165	
Diam. 6. Slot Size 55. Set from 205. ft. to 210. ft.	<u>Clay-gravel-green</u> Sand-fine-grav		178	
Drawdown is amount water level is leveled	Sand-gravel-fine		194 14	
(8) WELL TESTS:  Drawdown is amount water level is lowered below static level	Sand-gravel-clay	<del></del>	198	
Was a pump test made?   Yes X No If yes, by whom?	Sand-gravel-gray-loose		209 52	
d: gal./min. with ft. drawdown after hrs.	Clay-gray	209 2	215	
, , , , , , , , , , , , , , , , , , ,				
Air test gal./min. with drill stem at ft. hrs.				
Bailer test 50 gal/min. with 5 ft. drawdown after 1 hrs.				
tesian flow g.p.m.				
perature of water 55 Depth artesian flow encountered ft.	Work started 6_28 19 82 Comple	ted 7-3	1982	
(9) CONSTRUCTION: Special standards: Yes □ No 🖫	Date well drilling machine moved off of well	7-3	1982	
Well seal—Material usedcementgrout	<b>Drilling Machine Operator's Certification:</b>			
Well sealed from land surface to	This well was constructed under my direct			
Diameter of well bore to bottom of seal	and information reported above are true to my	_	dge and belief. 712., 19.82	
Diameter of well bore below seal	[Signed] (Drilling Machine Operator)		4LC., 19.UC	
Number of sacks of cement used in well seal	Drilling Machine Operator's License No	398		
* *	Water Well Contractor's Certification:			
and 6in • 0asing Water Well Contractor's Certification:  This well was drilled under my jurisdiction and this report is true.				
Was pump installed?	the best of my knowledge and belief.			
Was a drive shoe used?    Yes □ No Plugs Size: location ft.	Name Steinman Bros. Drilling Co. (Type or print)			
Did any strata contain unusable water?   Yes  No	Address 3023 SE Holly Ave. Milwo		Ore 97222	
Type of Water? depth of strata	1 00/20	10	. ,	
Method of sealing strata off	[Signed] (Water Well Contra			
Was well gravel packed? ☐ Yes 📆 No Size of gravel:	Contractor's License No	<b>-2</b> 2 <b>-</b> 82	19	
Gravel placed from ft. to ft.				