

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date
of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

G-7565

1640
MARI....0

State Well No. 55/W-8 da

State Permit No.

(1) OWNER: Willamette Valley Assembly Hall
Name of Jehovah's Witnesses
Address 1510 N. Pacific Hwy. / P.O. Box 36
Woodburn, Oregon 97071

(2) TYPE OF WORK (check):
New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL: Rotary Driven
Cable Jetted Dug Bored
(4) PROPOSED USE (check): Domestic Industrial Municipal
Irrigation Test Well Other

CASING INSTALLED: Threaded Welded
8" Diam. from 0 ft. to 116 ft. Gage 300
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS: Perforated? Yes No
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? Yes No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? Yes No If yes, by whom?
Well: gal./min. with ft. drawdown after hrs.
" " " " "
" " " " "
Baller test 20 gal./min. with 14 ft. drawdown after 1 hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION: Well seal—Material used Bentonite
Well sealed from land surface to 18 ft.
Diameter of well bore to bottom of seal 12 in.
Diameter of well bore below seal 8 in.
Number of sacks of cement used in well seal 4 sacks
Number of sacks of bentonite used in well seal 4 sacks
Brand name of bentonite National Bentnrite
Number of pounds of bentonite per 100 gallons of water
Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Marion Driller's well number ---
NE 1/4 SE 1/4 Section 8 T. 5S R. 1W W.M.
Bearing and distance from section or subdivision corner E 1/4
1065 feet south and 1206 feet west from
corner of Section 8, T. 5 S., R. 1W., W.M.

(11) WATER LEVEL: Completed well.
Depth at which water was first found --- ft.
Static level 36 ft. below land surface. Date 9/18/76
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing ---
Depth drilled 116 ft. Depth of completed well 116 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Top soil	0	2	
Clay, brown, fine sand	2	35	
Clay, gray, fine sand	35	49	
Clay, gray, fine sand	49	65	
Clay, gray, fine sand	65	81	
Brown sandstone	81	85	
Black course sand	85	107	
Sand and gravel	107	110	
Gray clay	110	115	
Black sand course gravel	115	116	

RECEIVED
NOV - 11 1976
WATER RESOURCES DEPT
SALEM, OREGON

Work started 9/15/ 19 76 Completed 9/18/ 1976
Date well drilling machine moved off of well 9/19/ 1976

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Rick S. Jeffrie Date 9/19/1976
(Drilling Machine Operator)
Drilling Machine Operator's License No. 0604

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Willamette Valley Assembly Hall of Jehovah's Witnesses
(Person, firm or corporation) (Type or print)
Address P.O. Box 36, Woodburn, Oregon 97071
[Signed] Sec.-Treas.
(Water Well Contractor)
Contractor's License No. 474 Date Oct. 10, 1976