

WATER WELL REPORT

STATE OF OREGON

Per RWN County should be main. Caw 9/24/82

#12 - Date rig moved off: 2/10/82 - per WWC 708 3/8/82 MARI. 1.65

RECEIVED

State Well No. FEB 17 1982

35/1W-34 ac

WATER RESOURCES DEPT SALEM, OREGON

(1) OWNER:

Name Edelweiss Farms
Address 12280 Denbrook
City Aurora State Or.

(2) TYPE OF WORK (check):

New Well [X] Deepening [] Reconditioning [] Abandon []
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Air [X] Driven [] Domestic [] Industrial [] Municipal []
Rotary Mud [] Dug [] Irrigation [] Test Well [] Other [X]
[] Bored [] Thermal: Withdrawal [] ReInjection []

(4) PROPOSED USE (check):

CASING INSTALLED: Steel [X] Plastic []
Threaded [] Welded [X]
8" Diam. from 0 ft. to 176 ft. Gauge 2.50

LINER INSTALLED:
" Diam. from ft. to ft. Gauge

(6) PERFORATIONS: Perforated? [X] Yes [] No
Type of perforator used Mills Knife
Size of perforations 1 1/4 in. by 4 in.
25 perforations from 145 ft. to 155 ft.

(7) SCREENS: Well screen installed? [] Yes [X] No
Manufacturer's Name
Type Model No.
Diam. Slot Size Set from ft. to ft.
Diam. Slot Size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
When a pump test made? [X] Yes [] No If yes, by whom? Driller
150 gal./min. with 21 ft. drawdown after 4 hrs.

Air test gal./min. with drill stem at ft. hrs.
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION: Special standards: Yes [] No [X]
Well seal—Material used Cement
Well sealed from land surface to 20 ft.
Diameter of well bore to bottom of seal 12 in.
Diameter of well bore below seal 8 in.
Number of sacks of cement used in well seal 30 sacks
How was cement grout placed? Pressure grouted from 20 ft. to land surface.

Was pump installed? Yes Type Sub. HP 7 1/2 Depth 126 ft.
Was a drive shoe used? [X] Yes [] No Plugs Size: location ft.
Did any strata contain unusable water? [] Yes [X] No
Type of Water? depth of strata
Method of sealing strata off
Was well gravel packed? [] Yes [X] No Size of gravel: ft.
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Clackamas Driller's well number 206
SW 1/4 NE 1/4 Section 34 T. 35 R. 1W W.M.
Tax Lot # Lot Blk Subdivision
Address at well location: 13280 Denbrook Aurora, Or.

(11) WATER LEVEL: Completed well.

Depth at which water was first found 123 ft.
Static level 47 ft. below land surface. Date 2/9/82
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 0
Depth drilled 176 ft. Depth of completed well 176 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with columns: MATERIAL, From, To, SWL. Rows include: Top soil, Clay, brown, Clay, sand, brown, fine, Clay, brown, Clay, blue, Clay, brown, Clay, blue, Clay, sand, blue, fine, Sand, black, fine, Gravel, sand, med. bl. fine, Sand, gravel, black, med., Clay, blue.

Work started 1/28 1982 Completed 2/9 1982
Date well drilling machine moved off of well 19

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Bob Keen Date 2/12, 1982
(Drilling Machine Operator)

Drilling Machine Operator's License No. 994

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name B. & G. Drilling (Type or print)
Address 10030 S. Backsburg Rd. Canby, Or.
[Signed] George J. Wainwright (Water Well Contractor)
Contractor's License No. 637 Date 2/12, 1982