NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 9731 within 30 days from the 324 within 30 days from the date of well completion.



WATER WELL REPORT RECEIVED

STATE OF OREGON

(Please type or print) (Please type or print)

not write above this line)

OCT 1 9 1953 well No. 15	20-36
STATE ENGINEEPPermit No.	
SALEM, OREGON	•

(1) OWNER:	(10) LOCATION OF WELL:	
Name Steve Kaufman	County Marjon Driller's well number 40	
Address R.R.2 Box 266 Silverton, Ore.	9 F v 6 Wv 6 v 76 - 7 5	
97381	Bearing and distance from section or subdivision corner	
(2) TYPE OF WORK (check):	Demails and distance from section of subdivision corner	
New Well 🔯 Deepening 🗌 Reconditioning 🗋 Abandon 🖂		
If abandonment, describe material and procedure in Item 12.	(11) WARRED I WILLY C.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well.	
Rotary 4 Driven D	Depth at which water was first found 63 ft.	
Cable	Static level 56 ft. below land surface. Date	
Dug Bored I Irrigation Test Well Other	Artesian pressure lbs. per square inch. Date	
(SCASING INSTALLED: Threaded Welded		
6	(12) WELL LOG: Diameter of well below casing	
" Diam from ft. to ft. Gage	Depth drilled 122 ft. Depth of completed well 119 ft.	
" Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size and structure of materials;	
	and show thickness and nature of each stratum and aquifer penetrated	
PERFORATIONS: Perforated? Yes No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.	
Type of perforator used	TEATHWAY AT	
Size of perforations in. by in.	4	
perforations from ft. to ft.	7 1	
perforations fromft. toft.	<u>clay brown</u> 1 26 clay grey 26 63	
perforations from ft. to ft.	sand grey crs. 63 77	
	conglom. med brown 77 117	
(7) SCREENS: Well screen installed? ☐ Yes ☑ No	gravel coarse loose grey 117 122-w.B	
Manufacturer's Name	121.0.0	
Type Model No		
Diam. Slot size Set from ft. to ft.		
Diam. Slot size Set from ft. to ft.		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
Was a pump test made? X Yes K No If yes, by whom?		
Yield: 86 gal./min. with 61 ft. drawdown after 1 hrs.		
Air "		
<u>"</u> " " " "		
Bailer test gal./min. with ft. drawdown after hrs.		
Artesian flow g.p.m.		
rature of motor X Donth autorion To		
Depth artesian now encountered	Work started 8-17 1973 Completed 8-18 1973	
(9) CONSTRUCTION:	Date well drilling machine moved off of well 8-18 1973	
Well seal—Material usedBent& Puddled clay	Drilling Machine Operator's Certification:	
Well sealed from land surface to	This well was constructed under my direct supervision	
Diameter of well bore to bottom of seal 95/8 in.	Materials used and information reported above are true to my best knowledge and belief:	
Diameter of well bore below seal6 in.	[Signed] Stewe Stadeli Date 9-10 1973	
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator)	
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No. 860	
Brand name of bentonite <u>National</u>	W. J. W. V. C. J. J. C. J. J. J. C. J. J. C. J. J. C. J.	
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:	
of water lbs./100 gals.		
Was a drive shoe used? 🖔 Yes 🗌 No Plugs Size: location ft.		
Did any strata contain unusable water? Yes No	Name R. Stadeli & Sons, Inc. (Person, firm or corporation) (Type or print)	
Type of water? depth of strata	Address Rte. 3. Box 169 - Silverton, OR	
Method of sealing strata off		
Was well gravel packed? ☐ Yes 🏝 No Size of gravel:	[Signed] Jaul S. Stalli (Water Well Contractor)	
Gravel placed from ft. to ft.		
ft.	Contractor's License No. 296 Date 8-31-73, 19	