NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

## WATER WELL REPORT

STATE OF OREGON

WYPIST.

		17/-
State	Well	No 75/3W-1

(Please type or print)

(Do not write above this line)

State Permit No.

or well completion.	16721 mm		
(1) OWNER:	(10) LOCATION OF WELL:		
Name Ralph W. Taylor	County Marion 'Driller's well num	nber 2285	
Address 1296 Court N.E.	¼ ¼ Section 1 T. 7S F	R. 3W W.M.	
Salem, WXXX Oregon 97301	Bearing and distance from section or subdivision		
(2) TYPE OF WORK (check):			
New Well 🗓 Deepening 🗌 Reconditioning 🗍 Abandon 🗎			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed we	11.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 46	ft.	
Rotary M Driven Domestic M Industrial Municipal	Static level 43 ft. below land surface. Date 4/1/80		
☐ Jetted ☐ ☐ Irrigation ☐ Test Well ☐ Other ☐	Artesian pressure lbs. per square inch. Date		
	and per begand		
(5) CASING INSTALLED: Threaded   Welded	(12) WELL LOG: Diameter of well be	low casing	
6	Depth drilled 80 ft. Depth of complet	ted well 80 ft.	
" Diam, from	Formation: Describe color, texture, grain size an	-	
" Diam. from ft. to ft. Gage	and show thickness and nature of each stratum with at least one entry for each change of formation		
(6) PERFORATIONS: Perforated? ☐ Yes ☒ No.	position of Static Water Level and indicate princ	ipal water-bearing strata.	
Type of perforator used	MATERIAL	From To SWL	
Size of perforations in. by in.	Topsoil	0 2	
perforations from ft. to ft.	Brown Clay	2 46	
perforations from ft. to ft.	Cemented Brown K Sand & Grave	46 73	
perforations from ft. to ft.	Brown Sand and XXXX Grawel	73 80	
(7) SCREENS: Well screen installed? ☐ Yes ☒ No			
Manufacturer's Name			
Type Model No.			
Diam Slot size Set from ft. to ft.			
Diam, Slot size Set from ft. to ft.			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		<u>D</u>	
a pump test made?  Yes X No If yes, by whom?	AFR 2 4 1980		
Yfeld: gal./min. with ft. drawdown after hrs.	WATER RESOURCES	PEF I	
Airtest 60 GPM for a period of 1, hour "	SALEM. OREGON		
n n			
Pailer test gal./min. with ft. drawdown after hrs.			
extesian flow g.p.m.			
Temperature of water Depth artesian flow encountered ft.	Work started 4/1/80 19 Completed	d 4/1/80 19	
(9) CONSTRUCTION:	Date well drilling machine moved off of well	4/1/80 <sub>19</sub>	
Portland Cement	Drilling Machine Operator's Certification:		
Well seal—Material used	This well was constructed under my		
Diameter of well bore to bottom of seal10	Materials used and information reported a best knowledge and belief	above are true to my	
Diameter of well bore below seal		Date 4/1/80, 19	
Number of sacks of cement used in well seal	(Drilling Machine Operator)		
How was cement grout placed? .pumpedinthruconductor	Drilling Machine Operator's License No	1.52	
pipe	Water Well Contractor's Certification:		
	This well was drilled under my jurisdic	ction and this report is	
Was a drive shoe used? X Yes □ No Plugs Size; location ft.	true to the best of my knowledge and belief.		
was a drive snoe used? We set in No Plugs Size: location	Name Willamette Drilling Co. (Person, firm or corporation)	(Type or print)	
Type of water? depth of strata	Address 7365 O'neill Rd. N.E. Sal		
Method of sealing strata off	D 11 2B.	/ ;	
	[Signed] Dalla Mells (Water Well Contra	ictor)	
Was well gravel packed? Tyes Who Size of gravel:	•	56± 4/1/80 10 10 10 10 10 10 10 10 10 10 10 10 10	
Gravel placed from ft. to ft.	Contractor's License No Date		