MAR/ 16758

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the
STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date of well completion.

RECEIVED APR 15 1969 STATE ENGINEER

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

State Well No. 7/3w-1 a c

State Permit No. G-4845

(1) OWNER:
Name Edward Zahara
Address 3425 Blossom Drive NE Salem, Oregon 97303

(2) TYPE OF WORK (check):
New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☐ Driven ☐
Cable ☒ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☒ Test Well ☐ Other ☐

CASING INSTALLED:
Threaded ☐ Welded ☒
8" Diam. from top ft. to 100 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:
Perforated? ☒ Yes ☐ No.
Type of perforator used Mills
Size of perforations 2 in. by 3/8 in.
328 perforations from 99 ft. to 65 ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:
Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.
Static level 35 ft. below land surface Date 4-7-69
Artesian pressure lbs. per square inch Date

(9) WELL TESTS:
Drawdown is amount water level is lowered below static level
Was a pump test made? ☒ Yes ☐ No If yes, by whom? Driller

d:	140	gal./min. with	15	ft. drawdown after	4	hrs.
	200	"	20	"	4	"
"	300	"	30	"	4	"

Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m. Date
Temperature of water Was a chemical analysis made? ☐ Yes ☐ No

(10) CONSTRUCTION:
Well seal—Material used Drill cuttings, Puddle Clay
Depth of seal 20 ft.
Diameter of well bore to bottom of seal 12 in.
Were any loose strata cemented off? ☐ Yes ☒ No Depth
Was a drive shoe used? ☒ Yes ☐ No
Did any strata contain unusable water? ☐ Yes ☐ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from ft. to ft.

(11) LOCATION OF WELL:
County Marion Driller's well number 1380
¼ ¼ Section T. 7S R. 3W W.M.
Bearing and distance from section or subdivision corner
Janet Pugh Land Donation

(12) WELL LOG:
Diameter of well below casing
Depth drilled 100 ft. Depth of completed well 100 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

MATERIAL	From	To	SWL
Top Soil	0	2	
Brown Clay	2	50	
Brown sand, clay, gravel	50	65	
Brown sand and gravel	65	100	35

Work started March 27, 1969 Completed April 7, 1969
Date well drilling machine moved off of well April 7, 1969 19

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Lyle Beckthold (Drilling Machine Operator) Date 4-8-69, 19
Drilling Machine Operator's License No. 151

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
NAME WILLAMETTE DRILLING COMPANY (Person, firm or corporation) (Type or print)
Address 7641 35th Ave. NE Salem, Oregon 97303
[Signed] Emil O. Beier (Water Well Contractor)
Contractor's License No. 2 Date 4-8-69, 19

(USE ADDITIONAL SHEETS IF NECESSARY)