

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

RECEIVED
WATER WELL REPORT

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date
of well completion.

MARI. 168

STATE OF OREGON

(Please type or print)

(Do not write above this line)

AUG 30 1976

State Well No.

State Permit No.

35/1W-34

WATER RESOURCES DEPT.
SALEM, OREGON

(1) OWNER:

Name Femrit Nursery Co.
Address Rt. 2 Box 79 Aurora, Oregon

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted
Dug Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

(5) CASING INSTALLED:

Threaded Welded

....." Diam. from0..... ft. to194..... ft. Gage250.....
.....6....." Diam. from183..... ft. to206..... ft. Gage250.....
....." Diam. from ft. to ft. Gage

(6) PERFORATIONS:

Perforated? Yes No.

Type of perforator used Morch
Size of perforations 3/8 in. by 2 in.
.....12..... perforations from194..... ft. to206..... ft.
..... perforations from ft. to ft.
..... perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is
lowered below static level

Was a pump test made? Yes No If yes, by whom? Driller
Yield: 50 gal./min. with 7 ft. drawdown after 2 hrs.
" " " " " " " "
" " " " " " " "
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.

Temperature of water 54; Depth artesian flow encountered ft.

CONSTRUCTION:

Well seal—Material used Bentonite
Well sealed from land surface to 35 ft.
Diameter of well bore to bottom of seal 12 in.
Diameter of well bore below seal 8 in.
Number of sacks of cement used in well seal sacks
Number of sacks of bentonite used in well seal 2 sacks
Brand name of bentonite National
Number of pounds of bentonite per 100 gallons
of water 200 lbs./100 gals.
Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Marion Driller's well number
1/4 1/4 Section 34 T. 3S R. 1E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 133 ft.
Static level 55 ft. below land surface. Date 3-20-76
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 8"

Depth drilled 206 ft. Depth of completed well 206 ft.

Formation: Describe color, texture, grain size and structure of materials;
and show thickness and nature of each stratum and aquifer penetrated,
with at least one entry for each change of formation. Report each change in
position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Soil brown	0	2	
Sandy clay brown	2	19	
Sandy clay grey	19	26	
Clay grey (sticky)	26	104	
Clay sandy grey	104	126	
Sand black (fine)	126	134	
Sand w small gravel black	134	138	
Sand w small gravel red	138	141	62
Sand black (heaving)	141	156	
Clay blue	156	175	
Sand & gravel black	175	191	
Gravel black W.B.	191	206	55

Work started 8-14 1976 Completed 8-23 1976

Date well drilling machine moved off of well 8-23 1976

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision.
Materials used and information reported above are true to my
best knowledge and belief.

[Signed] A.C. Stites Date 8-24, 1976
(Drilling Machine Operator)

Drilling Machine Operator's License No. 527

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is
true to the best of my knowledge and belief.

Name A.C. Stites (Type or print)
(Person, firm or corporation)

Address 28220 S. Dryland Rd. Seby, 97013

[Signed] A.C. Stites
(Water Well Contractor)

Contractor's License No. 533 Date 8-24, 1976