OBSERVATION WELL

WATER WELL REPORT

9/1W-2R

State Permit No.

File Original and First Copy with the STATE ENGINEER, SALEM, OREGON

STATE OF OREGON

1) OWNER:		(11) WELL TESTS: Drawdown is amount w. lowered below static lev	ater lovel : el	is
ame Etzell		Was a pump test made? 🖳 Yes 📋 No If yes, by whom	?	
Address RT / Box 300		Yield: 100 gal./min. with 110 ft. drawdown	after 2	hrs.
Stayton Stayton	n, Oregon	<u> </u>		<u>"</u>
2) LOCATION OF WELL:		<u> </u>	1	<u>"</u>
county Marion Owner's number, if any—		Bailer test gal./min. with ft. drawdown	ı after	hrs.
SE. 4 SE 4 Section S2 T. 9S R. 1W W.M.		Artesian flow g.p.m. Date		·
tearing and distance from section or subdivision		Temperature of water 57 Was a chemical analysis ma	de? 🗌 Ye	s XNo
caring and distance from section of subtrivial		(12) WELL LOG: Diameter of well	٦	inches.
	2. 7	Depth drilled $289\frac{1}{2}$ ft. Depth of completed we		
				- F-1
		Formation: Describe by color, character, size of material show thickness of aquifers and the kind and nature of t stratum penetrated, with at least one entry for each ch	he materio hange of f	ıl in each ormation.
		MATERIAL	FROM	TO
a) mype OF WORK (shock).		******	x2.	
3) TYPE OF WORK (check):	ditioning	14 Odn: 9 Oct.		
Tew Well		Top soil	0	2불
		Clay (orange)	2븡	4~
PROPOSED USE (check):	(5) TYPE OF WELL:	Tuff (light Brwn)	4	20
Domestic 🕱 Industrial 🗌 Municipal 🗌	Rotary Driven Cable K Jetted	Tuff (blue)	20	_26글
rrigation 🗌 Test Well 🗌 Other 🔲	Cable 🔼 Jetted 🗌 Dug 🗎 Bored 🗎	Basalt (fresh) crevice	26불고	1115
		encountered to full		
	eaded Welded	depth 26½ to 115'		
0 11/bam. from 0+1 ft. to		Tuff & clay -stone	115	129
" Diam. from ft. to ft. Gage		Basalt (fresh)	129	130衰
" Diam. from ft, to	ft. Gage	Sandstone (with wood & some	130	· · · · · · · · · · · · · · · · · · ·
(7) PERFORATIONS: Perforated? ☐ Yes ᡯ No		leaf fossils) old landsurfe		v 1 35늄
Type of perforator used		Basalt (fresh)	135	140
SIZE of perforations in. by in.		Basalt (fresh very hard)	140	172章
perforations from	ft. to ft.	Vescular basalt	172	174
perforations from		Basalt (fresh hard)	174	215
perforations from ft. to ft.		Vescular basalt	215	245
perforations from		Clay-stone & silt-stone	245	
perforations from		(with wood fragmts)	 	055
		old land surf	1 ACC	222
(8) SCREENS: Well screen i	nstalled 🗌 Yes 🔼 No	Vescular basalt	255	2092
Manufacturer's Name			-	
Гуре 1			 	<u> </u>
Diem Slot size Set from		Work started 2/19 19 62 Completed	4/4/0	52 19
Slot size Set from	It. to It.	Work started 2/19 19 02 Completed	_4/4/	
(9) CONSTRUCTION:		(13) PUMP:		
Was well gravel packed? ☐ Yes 🔁 No Size of gravel:		Manufacturer's Name	·····	
Gravel placed from ft. to ft.		Type:	H.P	·····
Was a surface seal provided? XYes ☐ No		W. I. D. H. Chatamant		
Material used in seal— Rock drill		Well Driller's Statement: This well was drilled under my jurisdiction	and this	report is
Did any strata contain unusable water? You of water? Depth of		true to the best of my knowledge and belief.	and min	TOPOL ID
Type of water? Depth of Method of sealing strata off	. pusuu			
		NAME George Robinson (Person, firm, or corporation)	Type or pri	nt)
10) WATER LEVELS:	1. 11. 14.	Address 3965 Hayesville Dr.	Saler	a, Ore
atic level 77 ft. below land	surface Date 4/4/62	07.0/0		
esian pressure lbs. per squ	uare inch Date	Driller's well number 21962	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
Accepted by:		[Signed] Honge H. Lobinson	~	
ed] Date	19	. ไ วัวนี	/4/62	10
(Owner)	•	License No. Date47		, 1J