State Well No. 5/16-9 N

PECFIVER	MARI.	17.19
The original and first copy of this report are to be SEP 2 2 1966 WATER WE filed with the		State Well
STATE ENGINEER, SALEM OREGON 97310 N.C.INEFESTATE O	F OREGON G-3885	State Permi
(1) OWNED.	(11) WELL MESMS.	Drawdown

_				
38R5	State	Permit	No.	_

(1) OWNER:	(11) WELL TESTS: Drawdown is amount lowered below static le	water leve	el is
Name T A Steele	Was a pump test made? △ Yes ☐ No If yes, by whom		
Address 2265 Hardcastle St	Yield: 110 gal./min. with 44 ft. drawdov	vn after	1 hrs.
Woodburn, Oregon	<u>" 145 " 62 "</u>		1 "
(2) LOCATION OF WELL:	<u>" 200 " 73 "</u>		4 "
County Marian Driller's well number	Bailer test gal./min. with ft. drawdo	wn after	hrs.
34 34 Section 9 T. 5S R. 1W W.M.	Artesian flow g.p.m. Date		· · · · · · · · · · · · · · · · · · ·
Bearing and distance from section or subdivision corner	Temperature of water Was a chemical analysis	made? 🔲	Yes X No
	(12) WELL LOG: Diameter of well below ca	sing	************
	Depth drilled 120 ft. Depth of completed we	11	120 ft.
			cture, and
	Formation: Describe by color, character, size of materia show thickness of aquifers and the kind and nature of stratum penetrated, with at least one entry for each c	tne mater hange of	ial in each formation.
	MATERIAL	FROM	то
(3) TYPE OF WORK (check):	Soil	0	4
New Well ∰ Deepening □ Reconditioning □ Abandon □	Brown sandy clay	4	25_
bandonment, describe material and procedure in Item 12.	Blue sandy clay	25	50
(4) PROPOSED USE (check): (5) TYPE OF WELL:	Brown sandy clay	50	70
Domestic Industrial Municipal Rotary Driven	Blue clay	70	<u>. 85</u>
Irrigation To Test Well Other Cable A Jetted	Black sand	85	90
Dug Bored	Black sand and gravel	90	96_
(6) CASING INSTALLED: Threaded Welded	Gravel E.	96	118
8 "Diam. from 0 ft. to 120 ft. Gage 14"	Blue clay	118	120
ft. Gage	· · · · · · · · · · · · · · · · · · ·		· · · · · · · · · · · · · · · · · · ·
(7) PERFORATIONS: Perforated? M Yes No			*
Type of perforator used Millknife			
Size of perforations 3/8 in. by 2 in.			
116 perforations from 108 ft. to 114 ft.			
perforations from ft. to ft.			7.20
perforations from ft. to ft.			
perforations fromft. toft.			
perforations from ft. to ft.			
(8) SCREENS: Well screen installed? ☐ Yes M No			
Manufacturer's Name		-	
Model No.		ļl	
Slot size ft. to ft.	Work stärted Sept 8 1966 Completed Se	pt 15	19 66
Diam Slot size Set from ft. to ft.		pt 15	19 66
(9) CONSTRUCTION:	(13) PUMP:		
Pudd ed Mud	(-5) 1 0.121		
Well Seal—Material used ill Seal	Manufacturer's Name	***************************************	
Depth of Seat	Type:	I.P	*************
Diameter of well bore to bottom of seal 12 in. Were any loose strata cemented off? Per No Depth	Water Well Contractor's Certification:		
Was a drive shoe used? \square Yes \square No \square	This wall was drilled and an area tout at the		
Was well gravel packed? Yes No Size of gravel:	This well was drilled under my jurisdiction a true to the best of my knowledge and belief.	and this	report is
Gravel placed from ft. to ft.	NAME John Truman Miller		
Did any strata contain unusable water! Yes X No	(Person, firm or corporation) (Ty)	pe or print)
Type of water? deprof strata	Address P O Box 42 Hubbard, Or	egon	*********
Method of sealing strata off	Drilling Machine Constants Line 32		
(10) WATER LEVELS:	Drilling Machine Operator's License No.	***********	•••••
	[Signed] John M. M. Ilu		
	(Water Well Contractor)	- 6	~ / /
Artesian pressure lbs. per quare inch Date	Contractor's License No. 277 Date Sept	16	, 19
(USE ADDITIONAL SH	EETS IF NECESSARY)		