NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT. SALEM, OREGON 97310 within 30 days from the date of well completion.

STATE OF ORGENTE IVE State W

State Permit No.

(Please type or print) MAY 191978 (Do not write above this line)

Ednd in Almohy	WATER RESOURCES DEPT.			
(1) OWNER:	(10) LACONTION OF WELL:			
Name Savin Mamis	County Marian Driller's well number			
Address RT 2 BOY 15117				
woodburn ore	88. 4 NE 4 Section / C T. 5 3 R. / W W.M			
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner			
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐				
If abandonment, describe material and procedure in Item 12.	(44)			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well.			
Rotary D Driven D	Depth at which water was first found			
Cable	Static level 25 ft. below land	l surface.	Date 5	
Dug	Artesian pressure lbs. per squ			1.0/10
CASING INSTALLED: Threaded Welded				
10 " Diam. from 0 ft. to 135 ft. Gage 250	(12) WELL LOG: Diameter of well below casing			
" Diam. fromft. toft. Gage	Depth drilled 135 ft. Depth of completed well 135 ft.			
" Diam. from ft. to ft. Gage	Formation: Describe color, texture grain size	and street		
	and blow differences and figure of pach etroi	nam and		
PERFORATIONS: Perforated? Yes No.	with at least one entry for each change of form position of Static Water Level and indicate pr			
Type of perforator used STAV H Way	MATERIAL	7	1	ng strata.
Size of perforations in. by 1/2 in.		From	То	SWL
\$00 perforations from 8.8 ft. to 120 ft.	TOP SOIL	0	2	ļ
perforations fromft. toft.	BROWN CLAY	2_	43	ļ <u>.</u>
perforations from ft. to ft.	GRAVEL E BLUE CLAY	43	47	
	BLUE CLAN - STICKEY	45	52	
(7) SCREENS: Well screen installed? Yes No	FINE SOND	52	58	
Manufacturer's Name	GRAVEL	58	61	<u> </u>
Type Model No.	FINE SAND	61	68	
Diam. Slot size Set from ft. to ft.	LARGE - BLEWIN GRAVEL	6.8	88	
Diam. Slot size Set from ft. to ft.	CLAY STOKE "GRAVEL	38	100	
(8) WELL TESTS: Drawdown is amount water level is	- GRAVEL	100	120	
lowered below static level	DARK BLAF CLOY	120	124	
Was a pump test made? Yes \(\subseteq \text{No If yes, by whom? } \(\mathbb{R} \) RILLER	SAND - FINE	124	126	
Yield: 500 gal./min. with 85 ft. drawdown after 5 hrs.	GANGE	126	131	
""	CLAY-DACK BLUE W/GENTL	131	134	
II	Green Clay	134	135	
Bailer test gal (min with # day day				
Artesian flow g.p.m. drawdown after hrs.				
Section 1				
nperature of water Depth artesian flow encountered ft.	Work started May 3 19 7 Complete	ed MA	116	1978
(9) CONSTRUCTION:	Date well drilling machine moved off of well	MAN		
Well seal-Material used Cement	Drilling Machine Operator's Certification:	* ***	//	1978
Well sealed from land surface to	This well was constructed under	ع م م د الم		
Diameter of well bore to bottom of seal 13 + in.		above a	superv re true	ision. to my
Diameter of well bore below seal				
Number of sacks of cement used in well seal	[Signed] (Drilling Machine Operator)	Date 17	MAY	19.78
How was cement grout placed?	Drilling Machine Operator's License No	17.00		
1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2				Carious and the same
	Water Well Contractor's Certification:			
	This well was drilled under my jurisditure to the best of my knowledge and but	ction and	i this ro	nort ie
Was a drive shoe used? XYes \(\text{No Plugs} \) No Plugs Size: location ft.	And wheate and being	ef.		P-01 10
Did any strata contain unusable water? Yes No	Name \\ \(\mathcal{U} \) \(\mathcal{C} \) \(\	11/13	29	
Type of water? depth of strata	Address 24037 5 SKY/ARe	(Typ	e or print)
Method of sealing strata off				
Was well gravel packed? ☐ Yes No Size of gravel:	[Signed] John W 130	M		
American Company of the Company of t	(Water Well Contra	ctor)		
araver praced from	Contractor's License No. 711 7 Date 5	-17		10 70