

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

RECEIVED JUN 2 1973

Well No.

35/1W-34

STATE ENGINEER SALEM OREGON

Permit No.

MARI 173

STATE ENGINEER, SALEM, OREGON 97310

within 30 days from the date of well completion.

(1) OWNER:

Name G.H. Savage
Address 4126 S.E. Milwaukie Ave
Portland, Oregon 97202

(2) TYPE OF WORK (check):

New Well [x] Deepening [] Reconditioning [] Abandon []

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [x] Driven []
Cable [] Jetted []
Dug [] Bored []

(4) PROPOSED USE (check):

Domestic [] Industrial [] Municipal []
Irrigation [x] Test Well [] Other []

CASING INSTALLED:

Threaded [] Welded [x]

12" Diam. from 0 ft. to 198 ft. Gage 1/4"
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? [x] Yes [] No.

Type of perforator used Millknife
Size of perforations 5/8 in. by 3 1/2 in.
110 perforations from 177 ft. to 182 ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? [] Yes [x] No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? [x] Yes [] No If yes, by whom? driller
Yield: 300 gal./min. with 49 ft. drawdown after 8 hrs.
350 " " 70 " " 8 "
400 " " 95 " " 8 "
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Cement
Well sealed from land surface to 40 ft.
Diameter of well bore to bottom of seal 18 in.
Diameter of well bore below seal 15 1/4 in.
Number of sacks of cement used in well seal 20 sacks
Number of sacks of bentonite used in well seal sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
Was a drive shoe used? [] Yes [x] No Plugs Size: location ft.
Did any strata contain unusable water? [] Yes [x] No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? [] Yes [x] No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Clackamas Driller's well number
1/4 1/4 Section 34 T. 3S R. 1W W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 148 ft.
Static level 51 ft. below land surface. Date 5/9/73
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing

Depth drilled 198 ft. Depth of completed well 198 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with columns: MATERIAL, From, To, SWL. Rows include Surface, Brown clay, Brown sandy clay, Blue sandy clay, Black sand, Broken sand & gravel.

Work started May 2 1973 Completed May 9 1973
Date well drilling machine moved off of well 19

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] John T. Miller Date May 10, 1973
(Drilling Machine Operator)

Drilling Machine Operator's License No. 26

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name John Truman Miller
(Person, firm or corporation) (Type or print)

Address P.O. Box 341 Hubbard, Oregon 97032

[Signed] John T. Miller
(Water Well Contractor)

Contractor's License No. 277 Date May 10, 1973