## V

## STATE OF OREGON WATER WELL REPORT



85/2WIIbb	)
 29717	

(START CARD) # \_\_\_\_

(as required by ORS 537.765)			
(1) OWNER: Weil Number: Weil Number: JOSEPH E. JOHNSON	(9) LOCATION OF WELL by legal description  County Marion Latitude	, ,	
Address 3748 74th Ave. S.E.	Township 8 South Nors, Range 2 West Eor W. WM.		
City Salem State Oregon Zip 97301	Section 11 NW 1/4 NW 1/4		
(2) TYPE OF WORK:	Tax Lot Lot Block Subdivi		
XX New Well Deepen Recondition Abandon	Street Address of Well (or nearest address) 3748 74th Ave. S.E. Salem, Orego		
(3) DRILL METHOD		,11	
XX Rotary Air Rotary Mud Cable	(10) STATIC WATER LEVEL:	: 2/L 01	
Other		5-24-91	
(4) PROPOSED USE:	Artesian pressure lb. per square inch. Date		
□ Domestic □ Community □ Industrial XX Irrigation	(11) WATER BEARING ZONES:		
☐ Thermal ☐ Injection ☐ Other	Depth at which water was first found 67 Ft		
(5) BORE HOLE CONSTRUCTION: 166		Rate SWL	
Special Construction approval Yes No Depth of Completed Well 166 ft Yes No Depth of Completed Well 166	67 Ft 159 Ft 90 GPM	25 '	
Explosives used			
HOLE SEAL Amount State To Sta			
$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$	(12) WELL LOG: Ground elevation		
0 202 100	Material From	To SWL	
		1	
How was seal placed: Method		7	
Other	Medium Boulder 7	10	
Backfill placed fromft, toft. Material	Multi-Colored Weathered Rock 10	21	
Gravel placed fromft, toft. Size of gravel	0) 2	42	
(6) CASING/LINER:	Didok Dabato 1100	67	
Diameter From To Gauge Steel Plastic Welded Threaded Casing: $8!! + 1\frac{1}{2}! 26\frac{1}{2}! .250$	Multi-Colored Broken Weathered Basalt WB 67	82	
Casing: 8" +1½' 26½'.250 X	Gray Basalt Firm 82	101	
	014) 24242	116	
		119	
Liner:	1 (014) 1014	141	
		143	
Final location of shoe(s) $26\frac{1}{2}$ Ft	023) 2322) =	145	
(7) PERFORATIONS/SCREENS:		149 159	
Perforations Method	Diddle (CDCdidi Diolici Document)	166 25 <b>'</b>	
Screens Type Material	Blue Gray Sandy Sticky Clay 159	100  23	
Slot Tele/pipe From To size Number Diameter size Casing Liner	Driller Recommended Pump Be		
From To size Number Diameter size Casing Liner	Set Between 130 Ft To 140 Ft.		
Alig 1 /- 4004	( 10 01	0.1	
70017 1991	Date started 6-18-91 Completed 6-24-	91	
WATER RESOURCES DES-	- (unbonded) Water Well Constructor Certification:		
(8) WELL TESTS: Minimum resting time is Thouse P7	I certify that the work I performed on the construction abandonment of this well is in compliance with Oregon was a second construction.	on, alteration, o	
☐ Pump ☐ Bailer ☒☒Air ☐ Artesian	standards. Materials used and information reported above are	e true to my be	
Yield gal/min Drawdown Drill stem at Time	knowledge and belief.		
90 166 Ft 1 hr.	<u> </u>	mber	
Air Test GPM May Fluctuate.	(bonded) Water Well Constructor Certification:	on obondo	
Temperature of water 50° Depth Artesian Flow Found Work performed on this well during the construction dates reported above.			
Was a water analysis done? Yes By whom	<ul> <li>work performed during this time is in compliance with</li> </ul>	th Oregon we	
Did any strata contain water not suitable for intended use?   Too little	construction standards. This report is true to the best of my	y knowledge an 1325	
□ Salty □ Muddy □ Odor □ Colored □ Other □	belief. MONDERS DRILLING, INC. WWC Number of Signed - D Monday Date 6-2		
	Signed / V   OV   Date 0-2	<u> </u>	