	ORIGINAL File Original, and Duplicate with the MAY 8 1956 WATER WELL DRII	LERS REPORT DO Not State Well No. 5/1W-166(1)
	STATE ENGINEER, SALEM OREGON CTATE ENCINEER STATE OF O	REGON X THE FILLIN
	(1) OWNER: SALEMK OREGON.	(10) WELL BUCK
	Name	Was a nump test made? Yes □ No If yes, by whom?
	The state of the s	Yield: 293 gal /min with 32
A STATE OF	Woodburn, Oregon	" 140 " 80 " 6 "
3	(2) LOCATION OF WELL:	n n
	County Marion Owner's number, if any-	Artesian flow g.p.m.
	R. F. D. or Street No.	Shut-in pressure lbs. per square inch.
	Bearing and distance from section or subdivision corner	Bailer test g.p.m. with ft. drawdown
	CORNER & N's of EV of the SE.	Temperature of water 56 Was a chemical analysis made? Was electric log made of well? Yes No
	Obc # #1 in Ser if 2 th Cooley	
-	WM in Mario County	(11) WELL LOG:
_	(3) TYPE OF WORK (check):	Diameter of well, 8 inches.
	ew well Deepening Reconditioning Abandon	Total depth 134 ft. Depth of completed well 134 ft.
	andonment, describe material and procedure in Item 11.	Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.
	(4) PROPOSED USE (check): (5) EQUIPMENT:	stratum penetrated, with at least one entry for each change of formation.
	Domostic II Industria	
	Irrigation Test Well Other Cable	
, in	Dug Weil	29 " 35 " Yellow silt & clay 35 " 65 " Blue Clay
	CASING INSTALLED: If gravel packed	65 " '70 " Process
•	nreaded Welded	,,
	FROM ft. to ft. Diam. Wall of Bore ft. ft	70, 104 " Blue Clay (Some Wate
•	Tob "134" 2" 2" YIXX	104 125 " Cemented sand & Gravel
	" " " " " "	" (Very little water)
	32 11 31 31 11	PLACK Sand & Grave 7 (Western)
	29 27 29 39 39 39 29 29 29 29 29 29 29 29 29 29 29 29 29	" " " LEADY HERE!
	" " " " " " " " " " " " " " " " " " "	Still drilling in above sand & gravel
	Type and size of shoe or well ring Size of grayel: Describe joint	n n
	Telded Francists 2/8 X 3	n n
	(7) PERFORATIONS: Mills	n n
	Type of periorator used	19 19 19 19 19 19 19 19 19 19 19 19 19 1
	ROM ft. to ft. perf per foot No of rown	n n
- 5	ROM ft. to ft. perf per foot No. of rows	77
	11 11 11 11 11 11 11 11 11 11 11 11 11	D D
	11 11 11 11 11 12 11	n n n n n n n n n n n n n n n n n n n
	19 19 29 29 29 29 39 39 39	" "
•	SCREENS: No Screens	"
6	Give Manufacturer's Name, Model No. and Size	" 125
		" " h6
	o construction: Puddled Clay	25 25 25 25 25 25 25 25 25 25 25 25 25 2
	Was a surface sanitary seal provided? Yes I No To what depth 20 ft.	" "
		Ground elevation at well site 20 feet above mean sea level.
1	TROM ft. to ft.	Work started april 109 56 Completed april 24 1 56
_)) i	Well Driller's Statement:
, 1	WETHOD OF SEALING	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
	(0) WATER TEXTOR O	TAT # 7 7 mm a b t m a m m
	Depth at which water was first found 65	(There is a second of the seco
	fonding level before	D
8	61	og ogrem, cregon
_		
r	Signed Hacks p. Kornovakom May 5, 1966	Signed]
•	Owner I	icense No. 2 Dated April 28
		19