16.

\* STATE OF OREGON
WATER WELL REPORT
(as required by ORS 537.765)

MARI 17863

5	3/2w	1294d
(START CARD) #	38688	3

(1) OWNER:	(9) LOCATION OF WELL by legal description:	
Name PEARMINE FARMS	County MARION Latitude Longitude	
Address 12223 River Rd NE	Township 55 N or S. Range 2W E or W. WM.	
City GERVAIS State ORE Zip 97026	Section 29 SE 4 NW 4	
(2) TYPE OF WORK:	Tax Lot Lot Block Subdivision	
	Street Address of Well (or nearest address) LANE TO WELL	
	ENTRANCE OPPOSITE 13063 RIVER RD. NE.	
(3) DRILL METHOD:		
Rotary Air Rotary Mud Cable	(10) STATIC WATER LEVEL:  30.5 ft. below land surface.  Date 5-21.92	
Other		
(4) PROPOSED USE:	Artesian pressure lb. per square inch. Date	
☐ Domestic ☐ Community ☐ Industrial ☐ Irrigation	(11) WATER BEARING ZONES:	
☐ Thermal ☐ Injection ☐ Other		
(5) BORE HOLE CONSTRUCTION:	Depth at which water was fuse found	
Special Construction approval $\square$ Yes $\square$ No Depth of Completed Well 80 ft.		
Explosives used Yes No Type Amount	From To Estimated Flow Rate SWL	
**	MAY 2 / 1992	
HOLE SEAL Amount Diameter From To   Material From To   sacks or pounds		
Diameter From To Material From To sacks or pounds 34" 0' 20' PORT. CEMENT O' 20' 38 SACKS	WATER RESOURCES DEP	
24" 0' 20' PORT. CEMENT O' 20' 38 SACKS	SALEM, ORLGON	
	(12) WELL LOG:	
	Ground elevation	
How was seal placed: Method A B C D E		
Other	Material From To SWL	
Backfill placed from ft. to ft, Material	DATACH 12 CASING W/A GOO O.D. D.DE	
Gravel placed from ft. to ft. Size of gravel	ALONG SIDE WHICH, ACCORDING TO	
(6) CASING/LINER:	WELL OWNER, WAS INSTALLED SOON	
· · ·	AFTER 12" WELL COMPLETION PURDOSE	
Casing:	OF 6", FOR GRAVEL FEED TO RESOLVE	
	A PROBLEM OF SAND ENTRANCE, NO	
	RECORD WAS MADE OF THIS WORK	
	, ,	
Liner:	WORK ACCOMPLISHED: AN INSDECTION	
	BY AW. R. DEDT AGENT OF THIS WELL'S	
Final location of shoe(s)	SURFACE SEAL WAS MADE. RESULT WAS	
(7) PERFORATIONS/SCREENS:	NO EFFECTIVE SEAL MATERIAL FOUND.	
Perforations Method	A SEAL ANNULUS WAS MADE W/A 6"	
Screens Type Material	DRILL RIT DRILL AROUND CASING-12"- of	
•	A WALL SOUD AROUND 6" CKSING	
Slot Tele/pipe From To size Number Diameter size Casing Liner		
A Size Number Braincier Size Casing Emer		
	WATER FOUND, WITH A VOID FROM 12'15';	
	AT 19', BLUE - BROWN HEAVY CLAY FOUND'	
	AT 70', SIDE DRILL STOPPED GROUT WAS	
	DUMDED THROUGH 3 -1 1/4" TREMIE DIDES	
	TO ENSURE THOROUGH DLACEMENT: 38 SALKE	
(8) WELL TESTS: Minimum testing time is 1 hour		
<del>-</del>	Date started MAY 14, 1992 Completed MAY 21, 1992	
Pump Bailer Air Artesian	(unbonded) Water Well Constructor Certification:	
	I certify that the work I performed on the construction, alteration, or abandon-	
Yield gal/min Drawdown Drill stem at Time	ment of this well is in compliance with Oregon well construction standards. Materials	
1 hr.	used and information reported above are true to my best knowledge and belief.	
1111		
	WWC Number	
	Signed Date	
(bonded) Water Well Constructor Certification:		
Temperature of Water Depth Artesian Flow Found I accept responsibility for the construction, alteration, or abandonment work per		
Was a water analysis done?  Yes By whom	formed on this well during the construction dates reported above. All work performed	
Did any strata contain water not suitable for intended use?   Too little	during this time is in compliance with Oregon well construction standards. This report is true to the best of my knowledge and belief.	
☐ Salty ☐ Muddy ☐ Odor ☐ Colored ☐ Other	WWC Number 633	
Depth of strata:	Signed / Mall Walday/ Date May 28, 1992	