	5/1W-1	7	N	1
tate Well No.				

DEGEIVER	182	\mathcal{T}			
NOTICE TO WATER WELL CONTRACTOR MAR 20 WATER V	OBSERVATION WELL 5/	-17	N.		
of this report are to be filed with the	OF OREGON State Well No.	N ' '	/ V /		
STATE ENGINEER, SALEM 10, OREGON (Please within 30 days from the date of well completion.	e type or print) G213\ State Permit NoG.	1968			
(1) OWNER:	(11) WELL TESTS: Drawdown is amount we lowered below static lew was a pump test made? X Yes No If yes, by whom	vel			
Name General Foods Corp. Address Birds Eye Division Well # 3	Yield: 750 gal./min. with 72 ft. drawdown		3½ hrs.		
	" 800 " 82 "	.i aitti	3 "		
Woodburn, Oregon	" " "	***************************************			
(2) LOCATION OF WELL:	Bailer test gal./min. with ft. drawdow	n after	hrs.		
County Marion Driller's well number	Artesian flow g.p.m. Date				
14 14 Section 17 T. 5S R. 1 W.	$\frac{M}{M}$ Temperature of water 52° Was a chemical analysis n	nade? 🗌 Y	es 🗶 No		
Bearing and distance from section or subdivision corner		15	16		
	(12) WELL LOG: Diameter of well below or		194 ft.		
	Formation: Describe by color, character, size of materia show thickness of aquifers and the kind and nature of a stratum penetrated, with at least one entry for each c	the materic hange of f	al in each ormation.		
	MATERIAL	FROM	то		
(3) TYPE OF WORK (check):	Surface	0	3		
Well Deepening Reconditioning Abandon	Carada harran alore	3	37		
andonment, describe material and procedure in Item 12.	Blue sandy clay	37	70		
(A) MAINE OF TAKE	Broken sand	70	90		
(4) PROPOSED USE (check): (5) TYPE OF WELL	Dide Clay	90	112		
Cable Z Jetted	Black sand	112	124		
	Gravel	124	136		
(6) CASING INSTALLED: Threaded Welded	Blue clay	136	<u> 155</u>		
16 " Diam. from 0 ft to 185 ft. Gage 5/16	GravelStatic level 36'2"	155	162		
" Diam, fromft. toft. Gage	Sticky blue clay	162	168		
Balluy blue Clay		168	187		
Julia Italia	Sandy gray clay	187	194		
(7) PERFORATIONS: Perforated? We Yes I No		-			
Type of perforator used Millknife					
Size of perforations 1/4 in. by 2 in. 315 perforations from 155 ft. to 162					
540 perforations from 123 ft. to 135.					
perforations from ft. to					
perforations from ft. to	i				
perforations from ft. to					
(8) SCREENS: Well screen installed ☐ Yes ☐ No					
Manufacturer's Name					
Model No.		1 2			
Diam. Slot size Set from			1962		
Diam. Stot size Set Home	ft. Date well drilling machine moved off of well Feb	12	1962		
(9) CONSTRUCTION:	(13) PUMP:				
Well seal-Material used in seal Bentonite Mud	Manufacturer's Name Jacuzzi				
Depth of seal 40 ft. Was a packer used? NO	Type: 9 stage Turbine	H.P. 100	<u> </u>		
Diameter of well bore to bottom of seal22 in.	*** / *** **				
Were any loose strata cemented off? Yes No Depth					
Was a drive shoe used? X Yes No	This well was drilled under my jurisdiction true to the best of my knowledge and belief.	and this	report is		
Was well gravel packed? ☐ Yes X No Size of gravel:	ann.				
Gravel placed fromft. to ft.	NAME John Truman Miller (Person, firm or corporation) (7)	Type or prin	-12		
Did any strata contain unusable water? ☐ Yes 🏝 No	Address P O Box 42 Hubbard, Or	lype or prin	ıtj		
Type of water? Depth of strata	Address 1 0 Dox 12 Hubbalu, Olegon				
Method of sealing strata off	Drilling Machine Operator's License No. 277	<i>!</i>			
(10) WATER LEVELS:	[Signed] John Trees 2 11				
Static level 33 ft. below land surface Date 2/7/62	[Signed] (Water Well Contractor)				
Artesian pressure lbs. per square inch Date	Contractor's License No. 277 Date Feb	7	1962		