NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM 10, OREGON within 30 days from the date of well completion.

WATER WELL\REPORT

STATE OF OREGON (Please type or print)

State Well No.

5//	w -	17	ser.)
	~ >	4//		

6-2532 State Permit No. 6-2324

(1) OWNER: Name BIRDS EYE DIV. OF GEN. TOOD	(11) WELL TESTS: Drawdown is amount water level is lowered below static level			
Name DIRIS EYE DIV. OF (TEN. TOOD) Address WOODBURN ORE	Was a pump test made? Yes □ No If yes, by whom? K STRASSER Yield: 850 gal./min. with 85 ft. drawdown after hrs.			
(2) LOCATION OF WELL:	Bailer test gal./min. with ft. drawdown after hrs.			
County // / Driller's Well number /	Artesian flow g.p.m. Date			
1/4 1/4 Section T. R. W. Bearing and distance from section or subdivision corner	Temperature of water 56 Was a chemical analysis made? Y Yes No			
Jedning and addition from bootson or warming and addition	(12) WELL LOG: Diameter of well below casing			
	Depth drilled 229 ft. Depth of completed well 228 ft.			
	Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.			
	MATERIAL FROM TO			
(3) TYPE OF WORK (check):	70P Sol4 0 7			
w Well Deepening Reconditioning Abandon Abandon abandonment, describe material and procedure in Item 12.	BLUE SANDY SILT 22 73			
	SAND SOME BINDER 73 112			
(4) PROPOSED USE (check): (5) TYPE OF WELL	SAND AND GRAVEL 1/2 /33			
Cable Z Jetted	1 133 152			
rrigation Test Well Other Dug Bored	CHRAVEL WITH BINDER 152 161			
(6) CASING INSTALLED: Threaded □ Welded	SAND SICT AND CLAY ICT 785			
20 "Diam. from 0 ft. to 9 ft. Gage 375				
12 " Diam. from				
	<u> </u>			
(7) PERFORATIONS: Perforated? Yes No				
Size of perforations in. by in.				
perforations from ft. to	ft.			
perforations from ft. to				
perforations from				
perforations from ft. to				
(8) SCREENS: Well screen installed Yes □ No				
nufacturer's Name JOHNSON				
pe Model No. Diam /25 Slot size Set from /90 ft. to 2/5	ft. Work started MAR 19963 Completed MAY 29 1963			
Diam. Slot size Set from ft. to ft.	With the state of			
(9) CONSTRUCTION:	(13) PUMP:			
Veil seal-Material used in seal CEMENT GROUT	Manufacturer's Name			
Depth of sealft. Was a packer used?	Type: H.P.			
Diameter of well bore to bottom of seal	Water Well Contractor's Certification:			
Vere any loose strata cemented off? □ Yes IX No Depth	This well was drilled under my jurisdiction and this report is			
Vas well gravel packed? Yes □ No Size of gravel:	true to the best of my knowledge and belief.			
ravel placed from	NAME KU STRASSER DRILLING CO			
old any strata contain unusable water? Yes No	Address SIIC SE SUUSETLAND TORMAD L ORE			
Type of water? SURFA (E Depth of strata 22 Method of sealing strata off (EMENT GROUT AND (ASI	ج.سر			
	Drilling Machine Operator's License No.			
(10) WATER LEVELS:	[Signed] Kabert J. Strasser			
tatic level 3 ft. below land surface Date 3/14/6 artesian pressure lbs. per square inch Date	(Water Well Contractor) Contractor's License No. Date Luke 1965			
Present Inc. per square their Date	Contractor's License No. Date , 1965			