STATE OF OREGON

WATER-WELL REPORT (as required by ORS 537.765)

RECEIVED

JAN & EASEGOPE or PRINT IN INKA

55/1W-18ac

MATER RESOURCES DE	PT (101 Official disc only)
(1) OWNER: SALEM, CREGON Name City of Woodburn	(10) LOCATION OF WELL by legal description: County Marion SW 4 NE 4 of Section 18 o
Address 210 Montgomery Street	Township 5S , Range 1W , WM.
City Woodburn State Oregon	(Township is North or South) (Range is East or West)
(2) TYPE OF WORK (check): 97071	Tax Lot Block Subdivision MAILING ADDRESS OF WELL (or nearest address)
· · ·	Water Dept. Shop Building - Well No. 1
New Well Deepening Reconditioning Abandon X	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL of COMPLETED WELL:
(3) TYPE OF WELL: (4) PROPOSED USE (check):	
Rotary Air Driven Domestic Industrial Musicipal Thermal:	Depth at which water was first found 35 ft.
Rotary Mud Dug Irrigation Withdrawal Reinjection	Static level See (12) ft. below land surface. Date
Other: Piezometric Goodnding Test	Artesian pressure —— Ibs. per square inch. Date ——
	(12) WELL LOG: Diameter of well below casing N/A
(5) CASING INSTALLED Steel Plastic Welded Welded	Depth drilled N/A ft. Depth of completed well of ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness
"Diam. from	and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
LINER INSTALLED: Steel Plastic Threaded Welded	MATERIAL From To SWL
Threaded	Abandonment Information:
	1. Well was perforated as indicated
(6) PERFORATIONS: Perforated? Yes \(\square\) No	in (6).
Size of perforations 3/8 in. by 2\frac{1}{25} in.	2. Sand came through perforations
Automation and the state of the	and filled hole up to 131 feet.
perforations from ft. to ft.	SWL rose from 35 feet up to 20
perforations from ft. to ft.	feet on 1/20/86.
(X) SCREENS: Well screen installed? Yes No	3. Pumped in approximately 5 vards
Mandfacturer's Name	(approx. 149 sacks) of nest cement
TypeModel No.	grout slurry from 131 feetwito 5 ft
Diam. Slot Size set from ft. to ft. to	4. Cut 12" casing off at floor level.
Diam. Slot Size Set from ft. to ft.	5. Placed premix concrete in top 5'
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	of hole (6 sacks).
a pump test made? Yes No Tyes, by whom?	
d: gal./min. with ft. drawdown after hrs.	
" " "	
Air test gal./min. with drill tem at ft. hrs.	
Bailer test gal./min. with ft. drawdown after hrs.	
esian flow g.g.m.	
nperature of water Depth ariesian flow encountered ft.	Date work started 1/20/86 /completed 1/22/86
(9) CONSTRUCTION: Special standards: Yes \(\square\) No \(\square\)	
Well seal—Material used	Date well drilling machine moved off of well 1/22 19 86
Well sealed from land surface to	(unbonded) Water Well Constructor Certification (if applicable):
Diameter of well bore to bottom of seal in.	This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore below seal	
Amount of sealing materialsacks □ pounds □	[Signed] Variable Vary Date 1-22, 1986
How was cement grout placed?	(bonded) Water Well Constructor Certification:
	Bond <u>FX490-652</u> Issued by: <u>American States Ins</u> (Surety Company Name)
Was pump installed? ft.	On behalf of Schneider Equipment, Inc.
Was a drive shoe used? Yes No Phy Size: location ft.	(type or print name of Water Well Constructor)
Did any strata contain unusable water?	This well was dylled under my virisdiction and this report is true to the
Type of Water? depth of rata	best of my knowledge and belief:
Method of sealing strata off	(Signed) Well Constructor)
Was well gravel packed?	(Dated)(Dated)
Gravel placed from ft. to ft.	and the second of the second o