		MART. 1.85		
	with the lot and mentioned			
TICE TO WATER WELL CONTRACTOR The original and first contraction	WATER WEI	LE REPORT #3 3/21	v-290	6
of this report are to be filed with the TATE ENGINEER, SALEM 10, OREGON	U 1964 STATE OF	OREGON Wer Ho.		<u></u>
within 30 days from the date of well completion.	E C ErtPlease type	e or print) G 5277 State Permit No.		
) OWNER:	e i constructione de la construction de la construc	(11) WELL TESTS: Drawdown is amount w lowered below static lev	ater level vel	is
ame City of Newberg		Was a pump test made? I Yes D No If yes, by whom? Driller		
ddress Newberg, Oregon		<u>vield: 1800 gal./min. with 9 ft. drawdown after 12 hrs.</u>		
		22 23 23		,,
2) LOCATION OF WELL:		Bailer test gal./min. with ft. drawdow	n after	hrs.
County Marion Driller's well number		Artesian flow g.p.m. Date		
1/4 1/4 Section T. R. W.M.		Temperature of water Was a chemical analysis made? Ves Ves		
Bearing and distance from section or subdivision corner		(12) WELL LOG: Diameter of well below casing		
Sec. 29 3S 2W		Depth drilled 101 ft. Depth of completed well 101 ft.		
		Formation: Describe by color, character, size of material and structure, and		
		show thickness of aquifiers and the kind and nature of stratum penetrated, with at least one entry for each c		
		MATERIAL	FROM	то
3) TYPE OF WORK (check):		Top Soil	0	5
	ditioning 🗌 🛛 Abandon 🗌	Sandy loam, brown	5	32
abandonment, describe material and proced	lure in Item 12.	Coarse sand, brown	32	35
W PROBATER USE (shock)	(5) TYPE OF WELL:	Brown silty sand w/water	35	48
4) PROPOSED USE (check):	Rotary $\Box$ Driven $\Box$	Grey sand	48	52
omestic 🗌 Industrial 🗌 Municipal 🔀	Cable 🔂 Jetted 🗌	Pea Gravel, Coarse gravel & sand	52	68
rigation 🗌 Test Well 🗌 Other 🔤 🗋	Dug 🗌 Bored 🗋	Cemented gravel	68	91
	aded 🗌 Welded 🖾	Loose gravel, water bearing	91	101
18# " Diam. from 0 ft. to 103 ft. Gage 375		Grey clay		
	ft. Gage			<u></u>
7) PERFORATIONS: Per	rforated? 🗶 Yes 📋 No			<u> </u>
ype of perforator used Mills Knife	ą			<u> </u>
ize of perforations 3/8 in. by	2 <sup>±/2</sup> in.			
520 perforations from 55				
			1	
	ft. to ft. ft. to ft.			
	ft. to ft.			
periorations from				
(b) DOMININ	alled? 🗌 Yes 🎇 No			+
anufacturer's Name		·		+
De M Diam Slot size Set from			5/29	19 64
Diam Slot size Set from Diam Slot size Set from		2/ ==	$\frac{5/23}{5/1}$	<u>19 64</u> 19 64
		Date well drilling monitor interest	<u></u>	
(9) CONSTRUCTION:		(13) PUMP:		
Well seal-Material used in seal Bentonite		Manufacturer's Name		
Depth of seal ft. Was a packer used? No		Туре: Н.Р		
'ameter of well bore to bottom of seal		Water Well Contractor's Certification:		
re any loose strata cemented off?	-тећан	This well was drilled under my jurisdiction	and this	s report is
। drive shoe used? ሺ Yes 📋 No ell gravel packed? 🛄 Yes 🚺 No	Size of gravel:	true to the best of my knowledge and belief.		-
vaced from ft. to		NAME A. M. Jannsen Drilling Company		
'rata contain unusable water?		(Person, firm or corporation) (Type or print)		
'er? Depth of strata		Address 21075 S. W. Tualatin Valle		
aling strata off		Drilling Machine Operator's License No. 2	Oregor 14	1
D I FVFI S.		511 1100()_		1
'R LEVELS:	E/20/Al	[Signed] (Water well Contractor	M	en
	d surface Date 5/29/64		5/2/	1964
lbs. per sq	uare inch Date			10.7.77.
	(USE ADDITIONAL)	SHEETS IF NECESSARY)		