	CLL REPORT 185 State Well No. 5/1w-18 L (1)
File Original and Duplicate with the STATE ENGINEER, SALEM, OREGON STATE ENGINEER	F OREGON AR State Permit No. G 43.5
(1) OWNER: Pavil The Eadlay of P	(11) WELL TESTS: Drawdown is amount water level is lawered below static level
Address Brown Street	Was a pump test made? Yes No If yes, by whom?  Yield: gal./min. with ft. drawdown after hrs.
Woodburn, Oregon	read. gat./min. with ft. drawdown after hrs.
(2) LOCATION OF WELL:	n n
County Marity Owner's number, if any	Bailer test 35 gal./min. with 13 ft. drawdown after 2 hrs.
NE 14 SW 14 Section 18 T. 5 S.R. 1 W. W.M.	Artesian flow g.p.m. Date  Temperature of water 57 was a chemical analysis made? □ Yes 18 No
Bearing and distance from section or subdivision corner Wall is	
located 950 ft. West and 410 ft. North of the N.E. corner of P. Raymond D.L.C. # 58	(12) WELL LOG: Diameter of well 6 inches.  Depth drilled 126 ft Depth of completed well 126
in Sec. 18, tsp. 5 S. R. 1 W, Marion County	
	show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.
	MATERIAL FROM TO
(3) TYPE OF WORK (check):	Top Soil 0 2
New Well	Silty yellow clay 2 33
If abandonment, describe material and procedure in Item 11.	Blue silty clay 33 72
PROPOSED_USE (check): (5) TYPE OF WELL:	Black Sand 72 87 Blue silty clay 87 112
Domestic ☐ Industrial ☐ Municipal ☐ Rotary ☐ Driven ☐ Cable <b>X</b> ☐ Jetted ☐	Blue silty clay 87 112 Silty Blue clay (some gravel 0 112 119
Irrigation Test Well Other Dug Bored	Black Sand & Gravel (Water) 119 126
(6) CASING INSTALLED: Threaded Welded X	
6 "Diam. from Top ft. to 126 ft. Gage •280	
" Diam. from	
(7) PERFORATIONS: Perforated?   Yes Y No	
Type of perforator used	
SIZE of perforations in. by in.	13.7
perforations fromft. toft.	119
perforations from ft. to ft.	1.7
perforations from ft. to ft.	
perforations fromft. toft.	
(8) SCREENS: Well screen installed ☐ Yes ▼ No	
Manufacturer's Name	
Type Model No.	
Diam. Slot size Set from ft. to ft. Slot size Set from ft. to ft.	Work started Feb. 9 19 57 Completed Feb. 15 19 57
	Work started Feb.9, 19 57 Completed Feb.15 19 57
(9) CONSTRUCTION: Was well gravel packed?   Yes No Size of gravel:	(13) PUMP:
Gravel placed fromft. toft.	Manufacturer's Name
Was a surface seal provided? 🔏 Yes 🗌 No To what depth? 24 ft.	Type: H.P.
Material used in seal— Puddled Clay	Well Driller's Statement:
Did any strata contain unusable water? ☐ Yes ☐ No  Type of water? Depth of strata	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Method of sealing strata off	
(10) WATER LEVELS:	NAME Orville Wymore (Person, firm, or corporation) (Type or print)
Static level 16 ft. below land surface Date 2-15-57	Address Box 101 Brooks, Oregon
Artesian pressure lbs. per square inch Date	Driller's well number 322
Log Accepted by:	[Signed] Proille Worrow , B. J.
[Signed] Date 1957	(Well/friller) License No. 88 Dat -15- 57
7-10-,18	A THE STATE OF THE
(USE ADDITIONAL SHE	ETS IF NECESSARY)