NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

NOTICE TO WATER WELL CONTRACTOR  The original and first copy of this report are to be  WATER WI	LL REPORT NGINEER 5	/1/22 .	- 19
NOTICE TO WATER WELL CONTRACTOR  The original and first copy of this report are to be filed with the  STATE ENGINEER, SALEM, OREGON 99301  STATE Of the within 30 days from the date of well completion.	F OREGON State Well No	/	
(1) OWNER:	(11) WELL TESTS: Drawdown is amount	water lev	el is
	lowered below static	level	
	Was a pump test made? ▼ Yes □ No If yes, by who Yield: 350 gal/min with 7/4 ft drawder		PLER'S
- NOOLE # 4 DOA 702A	Banymin with 14 10. arawac	wn after	4 hrs.
WOODRURN, OREGON 9707I	400 04	***	_4
(2) LOCATION OF WELL:	500 94		_4
County MARION Driller's well number 36		down after	hrs.
14 14 Section 19, 8, 50 T. 58 R. I WEST W.M.	Artesian flow g.p.m. Date		
Bearing and distance from section or subdivision corner	Temperature of water 54° Was a chemical analysis (12) WELL LOG: Diameter of well below to		
The state of the s		_	
	Depth drilled 182 ft. Depth of completed w		
	Formation: Describe by color, character, size of materishow thickness of aquifers and the kind and nature of	the mater	icture, and ial in each
	stratum penetrated, with at least one entry for each	change of	formation.
(9) TYPE OF WORK (-1, -1)	MATERIAL	FROM	TO
(3) TYPE OF WORK (check):	TOP SOIL	0	3
New Well Deepening Reconditioning Abandon		7	
andonment, describe material and procedure in Item 12.	BROWN CLAY	2	30
(4) PROPOSED USE (check): (5) TYPE OF WELL:	BROWN SAND	<del>70</del>	<del>- 37</del>
	BLUE CLAY	<del>31</del>	55-
Cable 14 Jetted 1	GREY SAND	55	62-
rrigation 12 Test Well Other Dug Bored	BLUE CLAY	62	75
(6) CASING INSTALLED: Threaded  Welded	BEACK SAND	75	80
	BEUR CLAY	80	105
TO Diam. fromft. to 182ft. Gage _250	BLACK SAND	I05	IIO-
"Diam. fromft. toft. Gage	BROWN SAND	IIO	II5
"Diam. fromft. Gage	GRAVEL	II5	128
(7) PERFORATIONS: Perforated? Types I No	BLUE SHALE	128	I30
Type of perforator used MTLLS	BLUE CLAY	130	I45
Size of perforations 3/8 in. by 3 1/3 in.	BROWN CLAY	<del>  I45</del>	I55
260 perforations from	BLUE CLAY	155	167
260 perforations from 167 ft. to 180 ft.	SAND & GRAVEL	167	182
perforations from ft. to ft.		+	
perforations fromft. toft.		1	ı.
perforations from ft. to ft.		-	
(8) SCREENS: Well screen installed? ☐ Yes ☑ No			-
Manufacturer's Name		+	
Model No.			
Slot size Set from ft. to ft.	Work started WADOW Q 407 Completed PR	TI 05	
Diam Slot size Set from ft. to ft.	Work started MARCH 8 49 Completed APR  Date well drilling machine moved off of well MARCH		<u> 19</u> 67
(9) CONSTRUCTION:	(13) PUMP:		19 67
Well seal—Material used in seal PUDDLE CLAY	Manufacturer's Name		
Depth of seal	Type:		
Diameter of well bore to bottom of seal in.	Lit		
Were any loose strata cemented off? [] 🚾 🖪 No Depth	Water Well Contractor's Certification:		
Was a drive shoe used? 🖪 Yes □ No 🍦	This well was drilled under my jurisdiction	and this	renort to
Was well gravel packed?   Yes No Size of gravel:	true to the best of my knowledge and belief.	. 61110 -	rebort 12
Gravel placed from ft. to ft.	NAME ा का कार्या		
Did any strata contain unusable water? 🍴 jes 🙎 No	NAME J. F. TERRELL (Person, firm or corporation) (Type or print)		
Type of water? depth d strata	Address RT # I, BOX 57, GERVAIS, (	REGON	ê
Method of sealing strata off			
(10) WATER LEVELS:	Drilling Machine Operator's License No.	19/	
Static level 16 ft. below land surface Date APRIL2531	[Signed] // // Yora Dale	, les	rell
Static level 16 ft. below land surface Date APRIL2531	(Water Well Contractor)		
Artesian pressure	Contractor splicense No. Too Date APRIL	25	., 19. 67
(USE ADDITIONAL SH	EETS IF NECESSARY)		