state Well No. State Permit No.

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 FILED OF OREGON within 30 days from the date of well completion.

EM. OREGON

1) OWNER:	(11) WELL TESTS: Drawdown is amount wat lowered below static level	er level is	
Name Henry Geschwill	Was a pump test made? Wes No If yes, by whom?		
Address 950 South Pacific Hiway	Yield: 500 gal./min. with 78 ft. drawdown a		
Woodburn, Oregon	<u>" 520 " 82 "</u>	2 "	
2) LOCATION OF WELL:	" "	"	
County Marion Driller's well number	Bailer test gal./min. with ft. drawdown	after hrs	
7.0	Artesian flow g.p.m. Date		
	Temperature of water 54 Was a chemical analysis mad	ie? 🔲 Yes 🗶 N	
Bearing and distance from section or subdivision corner	(12) WELL LOG: Diameter of well below casing	£	
	Depth drilled 130 ft. Depth of completed well	130 ft	
· · · · · · · · · · · · · · · · · · ·	Formation: Describe by color, character, size of material an show thickness of aquifers and the kind and nature of the stratum penetrated, with at least one entry for each chan	material in each	
· · · · · · · · · · · · · · · · · · ·	stratum penteriated, with at teast one entry for each chair	Je of formation	
(3) TYPE OF WORK (check):	MATERIAL F	ROM TO	
`. · · · · · · · · · · · · · · · · · · ·	Top soil	0 2	
Well To Deepening Reconditioning Abandon D	Brown clay	2 25	
Candonment, describe material and procedure in Item 12.	Brown sand	25 35	
(4) PROPOSED USE (check): (5) TYPE OF WELL:	Brown clay	35 45	
Domestic 🗶 Industrial 🗌 Municipal 📋 Rotary 🛄 Driven 🗆		45 65	
rrigation  Test Well Other  Cable  Jetted	Blue clay	65 80	
Dug 🗍 Bored 🗍	Black sand	80 95	
(6) CASING INSTALLED: Threaded  Welded	Blue clay	95 105	
10 " Diam, from 0 ft. to 130 ft. Gage 1/4"	Brown clay	105 108	
" Diam. fromft. toft. Gage	Coarse gravel	130	
	3		
(7) PERFORATIONS: Perforated? 4 Yes   No			
Type of perforator used Millknife  Size of perforations 3/8 in. by 3 in.			
Size of perforations 3/8 in. by 3 in.  310 perforations from 110 ft. to 128 ft.			
perforations from			
perforations fromft. toft.			
perforations fromft. toft.			
perforations from ft. to ft.			
(0) CODERATO			
(8) SCREENS: Well screen installed?   Yes I No			
Manufacturer's Name		1	
Model No.			
Dram. Slot size Set from ft. to ft.	Work started April 15 19 66 Completed Apri	.1 26 19 66	
Diam. Slot size Set from ft. to ft.		.1 27 19 66	
(9) CONSTRUCTION:	(13) PUMP:		
Puddied Mud			
Well seal—Material used in seal Puddled Mud  Depth of seal 18 # Wag & Backer used? no	Manufacturer's Name		
Depth of Seal	Type: H.P.		
Diameter of well bore to bottom of seal	Water Well Contractor's Certification:		
Were any loose strata cemented off? Tes No Depth	=		
Was a drive shoe used? M Yes □ No □ No □ Sze of gravel:	This well was drilled under my jurisdiction and true to the best of my knowledge and belief.	this report is	
Was well gravel packed? ☐ Yes I No Size of gravel:			
	NAME John Truman Miller (Person, firm or corporation) (Type or	**************************************	
Did any strata contain unusable water Yes No	(Person, firm or corporation) (Type or print)  Address P O Box 42 Hubbard, Oregon		
Type of water? depth of strata	WWW. WANTER WAYNOTTO & OLIC	'&A'IF''''	
Method of sealing strata off	Drilling Machine Operator's License No. 179		
(10) WATER LEVELS:	11/7 11/1		
Static level 20 ft. below and surface Date 4/26/66	[Signed] (Water Well Contractor)		
Artesian pressure lbs. per square inch Date	Contractor's License No. 277 Date April 27	. 66	
The first state of the state of	Date AVALL.21	19.50	

(USE ADDITIONAL SHEETS IF NECESSARY)