NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be STATE ENGWATER WELL REPORT filed with the

STATE ENGINEER, SALEM, OREGON 91610 TM OREGON within 30 days from the date of well completion.

lbs pe square inch Date

Artesian pressure

State Well No.

JUNE 29

Contractor's License No. ..... Date

5/1w-19@

of well completion.	G-3634 State Permit No	***************************************	
(1) OWNER:	(11) WELL TESTS: Drawdown is amount lowered below static le	water lev	/el is
Wame MRS.BETIE DRYDEN	Was a pump test made? X Yes \( \subseteq No. If yes, by whom		
Address RT.2 BOX 300 WOODBURN, OREGON.	Yield: 650 gal./min. with 67 ft. drawdow		6 hrs.
	" 550 " 58 "	WII WILLI	6 "
(2) LOCATION OF WELL:	" <b>4</b> 50 " <b>4</b> 8 "		6 "
	PRINTER 370 gal./min. with 44 ft. drawd	own after	
County MARION Driller's well number 1153	###### 330 g.p.m. race 37		D 6 F
34 34 Section <b>I9 - 30 T 5</b> R, <b>I W</b> W.M.	Temperature of water Was a chemical analysis		
Bearing and distance from section or subdivision corner	(19) WELL LOC.		
		ising	***************************************
	Depth drilled 197 ft. Depth of completed we		
	Formation: Describe by color, character, size of materia show thickness of aquifers and the kind and nature of stratum penetrated, with at least one entry for each c	il and stri	acture, and
· · ·	stratum penetrated, with at least one entry for each c	hange of	formation.
	MATERIAL	FROM	то
(3) TYPE OF WORK (check):	TOP SOIL	-	
New Well 🗶 Deepening 🗌 Reconditioning 🗎 Abandon 🗆	YELLOW CLAY	D G	3
andonment, describe material and procedure in Item 12.	YELLOW SANDY SILT	1	<u> 18</u>
(4) DDODOCED LICE (.1. 1) (5) MADE OF SUPER	BLUE SANDY SHALE	I8 .	40
(4) PROPOSED USE (check): (5) TYPE OF WELL:	BLACK SANDY SHALE	<b>AX4</b> 0	60
Domestic   Industrial   Municipal   Rotary   Driven   Cable <b>E</b> Jetted		60	80
Irrigation Test Well Other Dug Bored	BROWN STICKY SHALE	80	ĪÕÕ
(4) (4) (4)		100	II5
(6) CASING INSTALLED: Threaded  Welded	BROWN SAND	II5	OSI
TO Diam. from TOP ft. to 197 ft. Gage 250	SMALL GRAVEL	ISO	122
" Diam, fromft. toft. Gage	BLACK SAND SCATTERED GRAVEL	122	I35_
" Diam. fromft. toft. Gage	SAND & SHALE MIXED	I35	I45_
(7) PERFORATIONS: Perforated? ▼ Yes □ No	STICKY SHALE	I45	_I60_
vet fa	SANDY BLUE SHALE	I60	_I70_
2 2/0	BLACK SAND & GRAVEL	I70	I97
			<u> </u>
60 T25 It to 126			
60 perforations from 123 ft. to 126 ft. 460 perforations from 175 ft. to 197 ft. perforations from 175 ft. to 197 ft. ft. to 197 ft. ft. ft. to 197 ft.		ļ	
		<u> </u>	
perforations fromft. toft.			
perforations from ft. to ft.			
(8) SCREENS: Well screen installed? ☐ Yes ▼No			
Manufacturer's Name			-
Model No.	JU	VE.	
Slot size Set from ft. to ft.	Work started JUNE 13 1966 Completed		
Diam. Slot size Set from ft. to ft.	Date well drilling machine moved off of well JUNE		19 66
(9) CONSTRUCTION:	(13) PUMP:	29	19 66
Well seal-Material used in seal CEMEN & PUTTLE CLAY			
Depth of seal	Manufacturer's Name		
Diameter of well bore to bottom of seain.	Type: H.P.		
Were any loose strata cemented off? Tyes \( \bar{\pi} \) No \( \text{Depth} \) Depth \(	Water Well Contractor's Certification:		
Was a drive shoe used? Yes \( \) No	This well was dutied and a	_	
Was well gravel packed?  Yes No Size of gravel:	This well was drilled under my jurisdiction a true to the best of my knowledge and belief.	nd this	report is
Gravel placed fromft.	WITTA MANIGUE DE TET TAR		
Did any strata contain unusable water	NAME (Person, firm or corporation) (Type or print)		
Type of water? depth of strata	Address RT.2 BOX 276 SALMM, OREGO	N.	J.
Method of sealing strata off			*************
(10) WATER LEVELS:	Drilling Machine Operator's License No74	· E	
	[Signed] Emil O. Bulan	ز	
Static level 37 ft. belowland surface Date 6/29/66	(Water Well Contractor)		******
Artesian pressure lbs pe square inch Date	Contractor's Lieuwe N. 2: JUNE	29	88

(USE ADDITIONAL SHEETS IF NECESSARY)