NOTICE TO WATER WELL CONTRACTOR

The original and first copy

of this report are to be

filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

. 55/1W-21

(1) OWNER:	(10) LOCATION OF WELL:			
Name Carl T. Vistica	County Marion Driller's well no	ımber 🕽	1940	· · · · · · · · · · · · · · · · · · ·
Address 1640 C Northeast Salem OR 97303	14 14 Section 21 T. 58	r. 1W		W.M.
	Bearing and distance from section or subdivisi	on corner		
(2) TYPE OF WORK (check):				
New Well ☑ Deepening □ Reconditioning □ Abandon □				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 83 ft.			
Rotary Driven Domestic Industrial Municipal	Static level 30 ft. below land s	surface. I	Date 3/	29/76
Cable	Artesian pressure lbs. per squar	e inch. I	Date	
(5) CASING INSTALLED: Threaded □ Welded ₩	(12) WELL LOG: Diameter of well below casing 12			
	Depth drilled 245 ft. Depth of completed well 158 ft.			
ft. Gage	Formation: Describe color, texture, grain size			
Diam. fromft. toft. Gage	and show thickness and nature of each stratus	m and aq	uifer per	netrated,
(6) DEDEODATIONS.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.			
(6) PERFORATIONS: Perforated? ₩ Yes □ No.		T I	;1-0ea/ t/t	y atrutu.
Type of perforator used Mills Knife Perforator	MATERIAL	From	То	SWL
Size of perforations 7/16 in. by 2 3/4 in.	topsoil	0	2	
600 perforations from 121 ft. to 155 ft.	Brown Silty Clay	2	36	
perforations from ft. to ft.	Blue Silty Clay	36	58	
perforations from, ft. to ft.	Brown Sandy Clay	58	67	
(7) SCREENS: Well screen installed? Yes No	Blue Sticky Clay	67	79	
	Gray Sandy Clay	79	83	
; <u>'</u> *	Brown Comented Gravel	83	85	
Type Model No Diam Slot size Set from ft. to ft.	Gray Sandy Clay	85	91	
Diam. Slot size Set from ft. to ft.	Brown Cemented Gravel	91	92	
Diditi	Blue Sticky Clay Black Sandy Clay	92 118	118 120	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Black Cemented Sand & Gravel	120	155	
Was a pump test made? ▼ Yes □ No If yes, by whom? driller	Blue Sticky Clay	155	225	
	Brown Broken Shale, Sandy	225	245	
d: 300 gal./min. with 25 ft. drawdown after 1 hrs.		22)	~,,	•
" 550 " 55 " 1 "	1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -	t		
" 750	APIC 199			·
Bailer test gal./min. with ft. drawdown after hrs.	THE THE PARTY OF T			
esian flow g.p.m.	M*			
Temperature of water 52 Depth artesian flow encountered ft.	Work started 3/3/76. JREGON Complete	ad 3/3	0/76	19
(9) CONSTRUCTION:	Date well drilling machine moved off of well	3/3	0/76	19
Well seal-Material used Portland Cement	Drilling Machine Operator's Certification:			
Well sealed from land surface to	This well was constructed under my	direct	super	vision.
Diameter of well bore to bottom of seal	Materials used and information reported above are true to my best knowledge and belief.			
Diameter of well bore below sealin.				
Number of sacks of cement used in well seal 14 sacks	(Drilling Machine Operator)			
Number of sacks of bentonite used in well sal sacks	Drilling Machine Operator's License No.	752.		
Brand name of bentonite	Water Well Contractor's Certification:			
Number of pounds of bentonite per 100 alons				
of water	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.			
Was a drive shoe used? Yes No Plugs Size: location ft.	Name Willamette Diilling Co.			
Did any strata contain unusable water Tyes A No	(Person, firm or corporation) (Type or print)			
Type of water? depth of strata	Address 1450 Barnick Rd. NE Salem. OR 97303			
Method of sealing strata off	[Signed] & allas & Bells			
Was well gravel packed? Yes No Size of gravel:	(Water Well Contra		********	********
Gravel placed fromft. toft.	Contractor's License No. 561 Date 3	/30/76		. 19
				,