

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print) (Do not write above this line)

RECEIVED
OCT 20 1967
MARI 1939
5/1w-22

State Well No.

State Permit No.

(1) OWNER:

Name Alfred Aicher
Address Rt. 2 Box 129, Woodburn, Oregon

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted
Dug Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

CASING INSTALLED:

Threaded Welded
6" Diam. from top ft. to 129 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? Yes No.

Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.

Static level 45 ft. below land surface Date 10/16/67
Artesian pressure lbs. per square inch Date

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? Yes No If yes, by whom?
gal./min. with ft. drawdown after hrs.
" " " " " "
" " " " " "
Bailer test 25 gal./min. with 10 ft. drawdown after 1 hrs.
Artesian flow g.p.m. Dat
Temperature of water 56 Was a chemical analysis made? Yes No

(10) CONSTRUCTION:

Well seal—Material used Cement & Puddle clay
Depth of seal 20 ft.
Diameter of well bore to bottom of seal 10 in.
Were any loose strata cemented off? Yes No Depth
Was a drive shoe used? Yes No
Did any strata contain unusable water? Yes No
Type of water? dept of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(11) LOCATION OF WELL:

County Marion Driller's well number 1270
1/4 1/4 Section 22 T. 5 R. 1W W.M.
Bearing and distance from section or subdivision corner

(12) WELL LOG:

Diameter of well below casing

Depth drilled 129 ft. Depth of completed well 129 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

MATERIAL	From	To	SWL
Top Soil	0	2	
Yellow clay	2	18	
Brown sandy silt	18	65	
Brown sand & gravel	65	70	
Black sandy shale	70	90	
Black sand	90	93	
Black sand & gravel	93	102	
Gray clay	102	123	
Black sand	123	125	
Black sand & gravel	125	129	45

Work started 10/5/67 19 Completed 10/16/67 19
Date well drilling machine moved off of well 10/16/67 19

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Kenneth W. Morgan Date 10/16/67
(Drilling Machine Operator)

Drilling Machine Operator's License No. 474

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME WILLAMETTE DRILLING COMPANY
(Person, firm or corporation) (Type or print)

Address Rt. 2 Box 276, Salem, Oregon

[Signed] Ernie O. Beier
(Water Well Contractor)

Contractor's License No. 2 Date 10/16/67, 19