ORIGINAL File Original, and Dunliggte with the	WATER WELL DRIL	LERS REPORT Do Not State Well No. 5/1w-23 A ID
Duplicate with the STATE ENGINEER, SALEM, OREGON	1957 STATE OF OR	REGON I OC 1 Fill In C 211
(1) OWNER: A. H. Douthit	IGINEER MARY.	(10) WELL TESTS:
Address Rt. 2, Woodburn		was a pulmittest made? 12 Yes No If yes, by whom? Drlller
	1	" " " " " " " " " " " " " " " " " " "
	C. Salanda Car State, St. St. 192 of The grant of the gra	0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
(2) LOCATION OF WELL:	··· -	Artesian flow
County Marion Owner's number	r, if any—	Shut-in pressure lbs. per square inch.
R. F. D. or Street No.	the second of the second of the second of	Bailer test g.p.m. with ft. drawdown
Bearing and distance from section or subdivision	n corner	Temperature of water 50 Was a chemical analysis made? Yes No
	258 AS 1889 (201 - 44) \$271 D 2 44 ASS 150 (Was electric log made of well? ☐ Yes ☐ No
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	The state of the s	(11) WELL LOG:
		Diameter of well,
(3) TYPE OF WORK (check):	, , , , , , , , , , , , , , , , , , ,	Total depth 140 ft. Depth of completed well 140 ft.
	itioning Abandon	The state of the s
if abandonment, describe material and procedu		Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.
(4) PROPOSED USE (check):	(5) EQUIPMENT:	Oft. to 30 ft. Brown silt
Domestic 🗌 Industrial 🗎 Municipal 🖂	Rotary	30 " 50 " Light brown silt
Irrigation T Test Well Other	Cable 图	50 " 67 " Light blue silt
	Dug Well 🗆	67 " 88 " Cement gravel
(6) CASING INSTALLED:	If gravel packed	88 " 98 " Clay & silt mixed (light brown)
Threaded □ Welded □		98 " 100 " Dark brown silt
	Diameter from to	100 " 120 " Cement gravel
" top" to bottom " "	of Bore ft. ft.	120 " 126 " Sand & gravel
" " " " " " "	22 22	126 " 139 " Dark brown silt
))	"""	139 " 140 " Blue clay
. 39 39 39 39 39	"""	n n
" " " 6tr "	" "	"
Type and size of shoe or well ring Standard		n n
Describe joint Butt Weld		"
))
(7) PERFORATIONS:]	"
Type of perforator used Star		11 1)
7 A A A A A A A A A A A A A A A A A A A	length, by 1/4 in.	" "
FROM 67ft. to 88 ft. 5 perf r	per foot 2 No. of rows	1)
	" " 3 " " "	2)
	27 27 27 27 23	33
	" " " " "	7)
		23
SCREENS:	* ~1	27 27
Give Manufacturer's Name, Model No. a	ind Size	11 11 11 11 11 11 11 11 11 11 11 11 11
		27 27
(8) CONSTRUCTION:		77
Was a surface sanitary seal provided? [] Yes []		33 33 A A A A A A A A A A A A A A A A A
Were any strata sealed against pollution? Tes	3 🗆 No	Ground elevation at well site feet above mean sea level.
FROM ft. to	ft.	Work started July 14, 1956, Completed July 24, 1956
n n = n		Well Driller's Statement:
		This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
		NAME John W. Beck Well Drilling
Depth at which water was first found 30 ft.		(Person, firm, or corporation) (Typed or printed)
		Address Pt. 3 Por 45 gant
Standing level after perforating		Deiller II
		Driller's well number 369
[Signed] A Douth Dated	(Manet 1956)	[Signed] w Beck (Well Driller)
Owner		License No. 95 Dated July 31 , 19 ⁵⁶
	•	