RECEIVEDRECEIVED FEB6 1981 State Well No. 55/1W-26 AM WATER WELL REPORT DECO 4 1980 STATE OF OREGO WATER RESOURCES DEPT RESOURCES DEPT No. SALEM OREGON SALEM. ÖREGON (1) OWNER: (10) LOCATION OF WELL: Joseph Annen Marion Name County Driller's well number 7750 Annen Lane NE SE NW 4 Section 26 T.S R. / W Mt. Angel City Oregon Tax Lot # RIL Subdivision woodburn & Maniter Rd Address at well location: (2) TYPE OF WORK (check): New Well M Deepening Reconditioning Abandon (11) WATER LEVEL: Completed well. If abandonment, describe material and procedure in Item 12. Depth at which water was first found (3) TYPE OF WELL: (4) PROPOSED USE (check): Static level 40 ft. below land surface. Date 11 Industrial Driven ☐ Municipal Artesian pressure lbs. per square inch. Date Irrigation Dug □ Other Cable Thermal: Withdrawal ☐ Reinjection (12) WELL LOG: Depth drilled 500 (5) CASING INSTALLED: ft. Depth of completed well 480 Plastic Formation: Describe color, texture, grain size and structure of materials; and show Threaded Welded 2..."Diam. from +1 ft. to 480 ft. Gauge .250 thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level" Diam. from ft. to ft. Gauge and indicate principal water-bearing strata. LINER INSTALLED: MATERIAL From Topsoil 0 Clay Brown Med.] (6) PERFORATIONS: 23 Perforated? Yes Clay Brown Sandy Type of perforator used 23 3] Size of perforations Sandy Brown Med. 31 156,400 perforations from ft. to 265 ft. Sand Brown Med. w/ small 105,800 perforations from 265 ft. to 4**90** ft. gravel Clay Brwn Med. perforations from ft. to...... ft. Gravel Large - Sand Blk 106 WB (7) SCREENS: Well screen installed? ☐ Yes 🔀 No Clay Grey w/ sm gravel 106 258 Manufacturer's Name Sand Grey Fine & Med. 258 265 Clay Sandy Grey 265 338 Diam. Slot Size Set from ft. to ft. Sand Grey & Black Med. 347 338 WB Clav Grev 347 355 Drawdown is amount water level is lowered **WELL TESTS:** Sand Grey Course & Med. 355 365 below static level Clay Blue Med. 365 390 Was a pump test made? Yes No If yes, by whom? Clay Grey Sticky 390 495 gal./min. with ft. drawdown after 495 500 Air test 300-400 gal./min. with drill stem at 495ft. 35 r test gal./min. with___ ft. drawdown after Artesian flow Temperature of water Depth artesian flow encountered ft. Work started 10/17 19 80 Completed // - /2 19 80 Special standards: Yes □ No 🛚 (9) CONSTRUCTION: Date well drilling machine moved off of well Well seal—Material used Cement = 20 **Drilling Machine Operator's Certification:** Diameter of well bore to bottom of seal _______in. Number of sacks of cement used in well seal 28 sacks Drilling Machine Operator's License No. 1371 How was cement grout placed? Pressure Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name West Coast Drilling Co., Inc.

(Person, firm or corporation)

(Type or pr

WATER RESOURCES DEPARTMENT. SALEM, OREGON 97310 within 30 days from the date of well completion.

depth of strata

Was a drive shoe used?

Yes □ No

Was well gravel packed? ☐ Yes ☐ No

Method of sealing strata off

Type of Water?

Did any strata contain unusable water?

Yes X No

Gravel placed from ft. to ft. to ft.

Plugs Size: location ft.

Size of gravel: