NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the
STATE ENGINEER, SALEM, OREGON 97310
Within 30 days from the date
of well completion.

OREGON (Please type or print)

G-3580

State	Well	No.	5/	שון	۔۔۔ ،	24	2	G
-------	------	-----	----	-----	--------------	----	---	---

State Permit No.

(1) OWNER:	(11) WELL TESTS: Drawdown is amount water level lowered below static level	rel is				
Name ED C. BARCHENGER	Was a pump test made? Yes No If yes, by whom? STADEL!					
Address RTQ BOX 70 B	Yield: 60 gal./min. with TOTALft. drawdown after	4 hrs.				
WOOD BURN OREGON	" "	<u>"</u>				
(2) LOCATION OF WELL:	,, ,, ,, ,, ,, ,, ,, ,, ,, ,, ,, ,, ,,					
County MARION Driller's well number	Bailer test gal./min. with ft. drawdown after	hrs.				
14 14 Section 26 T.5 S R. 1W W.M.	Artesian flow g.p.m. Date	17				
Bearing and distance from section or subdivision corner	Temperature of water 3 4 Was a chemical analysis made?	Yes No				
	(12) WELL LOG: Diameter of well below casing	£				
	Depth drilled 160 ft. Depth of completed well 15	ft.				
	Formation: Describe by color, character, size of material and str show thickness of aquifers and the kind and nature of the mater stratum penetrated, with at least one entry for each change of	ucture, and				
	show thickness of aquiters and the kind and nature of the mater stratum penetrated, with at least one entry for each change of	formation.				
	MATERIAL FROM	то				
(3) TYPE OF WORK (check):	TARCALL AND CLIT D	10				
Well Deepening Reconditioning Abandon	BROWN CLAN	30				
andonment, describe material and procedure in Item 12.	BROWN SANDAND CHI 30	52				
(4) PROPOSED USE (check): (5) TYPE OF WELL:	SAND AND GRAVEL 52	72				
Domestic Industrial Municipal Rotary Driven	BROWN CLAY 75	92				
Irrigation Test Well Other Cable Jetted	GRAVEL WATER BEARING 92	100				
Dug 🗋 Bored 🗋	BLUE CLAY 100	135				
(6) CASING INSTALLED: Threaded Welded Z	SANDY CLAY 135	145				
8 "Diam. from D ft. to 149 16" ft. Gage 4WALL	WATER BEARING	•				
" Diam. from ft. to ft. Gage	BLUE CLAY 143	160				
" Diam. from ft. to ft. Gage						
(7) PERFORATIONS: Perforated? Yes No						
Type of perforator used MILLS KNIFE						
Size of perforations 3/c in. by 2 in.						
perforations from 86 ft. to 14.5 ft.						
perforations from ft. to ft.						
perforations from ft. to ft.						
perforations from ft. to ft.						
perforations from ft. to ft.						
(8) SCREENS: Well screen_installed? ☐ Yes WNo						
Manufacturer's Name		<u></u>				
Model No.		<u></u>				
Slot size Set from ft. to ft.	Work started 6-8 1966 Completed 6-21	1961				
Diam. Slot size Set from ft. to ft.	Date well drilling machine moved off of well 6-22	1966				
(9) CONSTRUCTION:	(13) PUMP:					
Well seal—Material used in seal BENTONITE	Manufacturer's Name NONE					
Depth of seal 20 ft. Was a packer used? GAANEL	Type: HP					
Diameter of well bore to bottom of sealin.	444					
Were any loose strata cemented off? Ves No Depth	Water Well Contractor's Certification:					
Was a drive shoe used? Nes □ No	This well was drilled under my jurisdiction and this	report is				
Was well gravel packed? X Yes □ No. Size of gravel:	true to the best of my knowledge and belief.	Toport 25				
Gravel placed from 20 ft 10 72 ft.	NAME WILLIA M. J. STENNET T. (Person, firm or corporation) (Type or print)					
Did any strata contain unusable water TYes TYNo	(Person, firm or corporation) (Type or print)					
Type of water? depth of strata	Address 361 WARNER MILNE RD ORECONCITY					
Method of sealing strata off	Drilling Machine Operator's License No. 170-17/	•				
(10) WATER LEVELS:	Marie 1 The self	************				
Static level 44 ft. below land surface Date 6-21-66	[Signed] Water Well Contractor)	************				
Artesian pressure lbs. per square inch Date	Contractor's License No. 5 Date June 23	1026				
(IISE ADDITIONAL OF	BEETE THE STREET AND	, 19129				