NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310

WATER WELL REPORT ARI. 204 STATE OF OREGON

(Please type or print)

State Well No.55/1W - 28

within 30 days from the dage 6 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	above this line) State Permit N	₹o	1444A74A94- p4 465575/	~f************************************
(1) OWNER: NOV - 91977	(10) LOCATION OF WELL:			<u>_</u>
Name Gordon SeelyWATTE RESOURCES DEPT.	County Marion Driller's well number 2093			
Rt. 2 Box 40 Woodburn Of ago 0007071	14 14 Section 28 T.5S	R. 1W	2073	*** *
7	Bearing and distance from section or subdivisi		<u></u>	W.1
(2) TYPE OF WORK (check):	bearing and distance from section of subdivisi	ion corne	<u>r</u>	
New Welk⊠ Deepening □ Reconditioning □ Abandon □				· · · · · · · · · · · · · · · · · · ·
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 55			
Rotary Driven Domestic Triductrial Demostic				101 /7:
Cable	A.J. J.			21//
	Artesian pressure lbs. per squar	re inch.	Date	
CASING INSTALLED: Threaded □ Welded	(12) WELL LOG: Diameter of well h	h -1		mann
8 Diam from top ft. to 168 ft. Gage 250	Depth drilled 195 ft. Depth of compl			_
" Diam. from	Formation: Describe color, texture, grain size			
" Diam. from ft. to ft. Gage	and snow inickness and nature of each stratu	m and a	anifon ne	
PERFORATIONS: Perforated? X Yes No.	with at least one entry for each change of forma position of Static Water Level and indicate prin	tion Rene	art asch	ahamaa i
Type of perforator used Mills Knife	MATERIAL			Γ
Size of perforations 3/8/ in, by 2½ in.		From	То	SWL
560 perforations from 65 ft. to 140 ft.	Topsoil Yellow Clay	0	1	
perforations from ft. to ft.	Blue Clay	$\frac{1}{\sqrt{2}}$	42	
perforations fromft. toft.	Brown Sand adn Gravel	<u>42</u> 55	55	
(f) COPERIO	Cemented Gravel	80	80 140	
(7) SCREENS: Well screen installed? ☐ Yes ☐ No	Blue &xxx clay	140	195	
Manufacturer's Name				
Type Model No Blam Slot size Set from ft. to ft.				
Diam. Slot size Set from ft. to ft.				
(8) WELL TESTS: Drawdown is amount water level is lowered below static level				
Was a pump test made? Wes E No If yes, by whom? driller				·
Yield: 250 gal./min. with 62 ft. drawdown after 3 hrs.				
H 11				
II II III II				
Bailer test gal./min. with ft. drawdown after hrs.				
Artesian flow g.p.m.				
perature of water Depth artesian flow encountered ft.	Work started 9/1/77 19 Complete		 _	
	The state of the s	$\frac{d}{2} \frac{9}{21}$	<u>/// </u>	19
(9) CONSTRUCTION:	Date well drilling machine moved off of well	9/21	<u>/77</u>	19
Well seal—Material used Portland Cement	Drilling Machine Operator's Certification:			
Well sealed from land surface to 19 ft.	This well was constructed under my Materials used and information reported a heat knowledge and helical	direct	superv	vision.
Diameter of well bore to bottom of seal12	best knowledge and belief.	anove ai	re true	to my
Diameter of well bore below seal	[Signed] Manual M. Martin I	Date 9/	22/77	.19
How was cement grout placed? Poured in from the top	Drilling Machine Operator's License No	530	, 6	,
was centent grout placed passassassassassassassassassassassassass	Machine Operator's License No		2	************
	Water Well Contractor's Certification:			
	This well was drilled under my jurisdic	tion and	this re	port is
Was a drive shoe used Yes No Plugs Size: location ft.	are to me pear of my knowledge and belie	ef.		v 1D
Did any strata contain unusable water? Y No	Name Willamette Drilling Co. (Person, firm or corporation)	/W		
Type of water? depth of strata	Address 1450 Barnick Rd, NE Salem	ι ΟΣ (πλρε	e or print	;) }
Method of sealing strata off	(s) and (b)		······································	
Was well gravel packed? ☐ Yes No_ Size of gravel:	[Signed] Land (Water Well Contract		-	************
Gravel placed fromft.	= = = = = = = = = = = = = = = = = = = =		דו	
	Date	9/22/7	1	10