

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date
of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

MAK 20668

State Well No.

State Permit No.

75/2w-22

(1) OWNER:

Name L & R Nursery

Address 6505 Fruitland Rd.

Salem, Oregon 97301

(2) TYPE OF WORK (check):

RE-Seal Only

New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Drilled ☐
Jettied ☒
Bored ☐

(4) PROPOSED USE (check):

Domestic ☐ Industrial ☐ Municipal ☐
Irrigation ☒ Test Well ☐ Other ☐

(5) CASING INSTALLED:

Threaded ☐ Welded ☐

" Diam. from ft. to ft. Gage

" Diam. from ft. to ft. Gage

" Diam. from ft. to ft. Gage

(6) PERFORATIONS:

Perforated? ☐ Yes ☐ No.

Type of perforator used

Size of perforations in. by in.

perforations from ft. to ft.

perforations from ft. to ft.

perforations from ft. to ft.

(7) SCREENS:

Well screen installed? ☐ Yes ☐ No

Manufacturer's Name

Type Model No.

Diam. Slot size Set from ft. to ft.

Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

a pump test made? ☐ Yes ☐ No If yes, by whom?

Yield: gal./min. with ft. drawdown after hrs.

" " " "

" " " "

Artesian flow gal./min. with ft. drawdown after hrs.

Artesian flow g.p.m.

Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Portland Cement

Well sealed from land surface to 20 ft.

Diameter of well bore to bottom of seal 24" in.

Diameter of well bore below seal 10 in.

Number of sacks of cement used in well seal 62 sacks

How was cement grout placed? pumped in thru conductor pipe

Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft.

Did any strata contain unusable water? ☐ Yes ☐ No

Type of water? depth of strata

Method of sealing strata off

Was well gravel packed? ☐ Yes ☐ No Size of gravel:

Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Marion

Driller's well number 2278

1/4 1/4 Section 22 T. & 7S R. 2W W.M.

Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found ft.

Static level ft. below land surface. Date

Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing

Depth drilled ft. Depth of completed well ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Well resealed only, cap was never removed. Static was not checked. Well side-drilled on all sides to at least 7 inches greater on all all side of the casing leaving a minimum sized hole of 24 inches.. Water Master Dick Nimrod was present during sealing procedure. Well was side-drilled by Ron Morton but was resealed by Dallas Beier.			

RECEIVED

JUL 13 1980

WATER RESOURCES DEPT
SALEM, OREGON

Work started 7/1/80 19 Completed 7/3/80 19

Date well drilling machine moved off of well 7/3/80 19

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Ron Morton Date 7/7/80, 19
(Drilling Machine Operator)

Drilling Machine Operator's License No. 536

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name Willamette Drilling Co.
(Person, firm or corporation) (Type or print)

Address 7365 O'Neil Rd. N.E. Salem, Oregon 97303

[Signed] Dallas Beier
(Water Well Contractor)

Contractor's License No. 561 Date 7/7/80, 19

(USE ADDITIONAL SHEETS IF NECESSARY)