NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report.

are to be filed with the

WATER WELL REPORT.

WATER RESOURCES DEPARTMENT, JUL 2 2 1970STATE OF OREGON SALEM, OREGON 97310 (Please type or print) within 30 days from the data RESOURCES DEPT of well completion. WATER RESOURCES DEPT CALES OF COLUMN CALES OF CALES OF COLUMN CALES OF CALES OF

MARI. State Well No. 55/1W-31

(1) OWNER:	(10) LOCATION OF WELL:			
Name Joseph Messer	County Marion Driller's well number 2124			
Address 9974 Mt. Angel-Gervais Rd. NE	31 T.5S	R. 1W		W.M.
Gervais, Oregon 97026	Bearing and distance from section or subdivisi		,	******
(2) TYPE OF WORK (check):		OIL COINCI		
New Well 🔀 Deepening 🗌 Reconditioning 🗍 Abandon 🗍				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	·all		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 81 ft.			
Rotary Driven Domestic Industrial Municipal	Static level 15 ft. below land		ate 2/	
Cable 15 Jetted	Artesian pressure lbs. per squar			10/ /0
CASING INSTALLED: Threaded D Welded M	ins. per squar	e men. D	ate	
Timedada [Weided M	(12) WELL LOG: Diameter of well below casing			
1.0° Diam. from top ft. to 17.6 ft. Gage 250 ft. Gage ft. Gage	Denin offiled 1/6 tt Denth of completed well 3/6 &			
" Diam, from	Formation: Describe color, texture, grain size and structure of materials.			
Diani, Itoli	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in			
PERFORATIONS: Perforated? Y Yes No.	position of Static Water Level and indicate prin	icipal wate	r-bearin	nange in g strata.
Type of perforator used Mills Knife Perforaton	MATERIAL	From	то	SWL
Size of perforations 3/8 in. by 2½ in.	Topsoil	0	1	
290 perforations from 85 ft. to 110 ft.	Yellow Chay	1	53	
120 perforations from 163 ft. to 175 ft.	Blue &xx clay	53	81	
perforations from ft. to ft.	Brown Sand and Gravel	81	112	······································
(7) CODEING.	Blue KXXX Clay	112	115	
(7) SCREENS: Well screen installed? ☐ Yes 🛱 No	Black Sand	115	127	
Manufacturer's Name	Sandy Gray Clay	127	152	
Type Model No ft. to ft.	Black Sand	152	157	
Diam. Slot size Set from ft. to ft.	Blue Clay	157	160	
	Black Sand and Gravel	160	176	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level				
Was a pump test made? MYes DNo If yes, by whom? driller				
Yield: 700 gal./min. with 7 ft. drawdown after 2 hrs.				
" " "				
" " " "				
Artesian flow g.p.m.				····
perature of water Depth artesian flow encountered ft.		$\frac{2}{10}$	⁷⁸	19
(9) CONSTRUCTION:	Date well drilling machine moved off of well	2/10/	<u>′78</u>	19
Well seal—Material used Portland Cement	Drilling Machine Operator's Certification:			
Well sealed from land surface to 19 ft.	This well was constructed under my Materials used and information reported	direct s	uperv	ision.
Diameter of well bore to bottom of seal in.	best knowledge and belief.			•
Diameter of well bore below sealin,	[Signed] Rend W. Wigner [] (Drilling Machine Operator)	Date .2/1	1/78	19
Number of sacks of cement used in well seal sacks	Drilling Machine Operator) Drilling Machine Operator's License No			
How was cement grout placed? poured in from the top	Drining Machine Operator's License No			
	Water Well Contractor's Certification:			
	This well was drilled under my jurisdic true to the best of my knowledge and beli	ction and	this rep	port is
Was a drive shoe used? ☒ Yes ☐ No Pluß Size: location ft. Did any strata contain unusable water? ☐ Yes ☒ No	Name Willamette Drilling Co.			
Type of water? dealt of strata	(Type or print)			
	Address 1450 Barnick Rd, NE Sale	am, Ore	gon	<u>9.7.30</u> 3
Method of sealing strata off	[Signed] Dallas T Decis	***********		
Was well gravel packed? ☐ Yes 🐧 № Size of gravel:	(Water Well Contra		**	**********
Gravel placed from ft. to ft.	Contractor's License No. 561 Date	<u>2/11/78</u>	·····,	19
/ ITEM A TOTAL				