

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date
of well completion.

2/37
MARI...

WATER WELL REPORT

RECEIVED

STATE OF OREGON
(Please type or print)

APR 25 1973

State Well No.

5S/1W-32db

(Do not write above this line)

STATE ENGINEER

Permit No.

G-6115

SALEM, OREGON

G-6115

(1) OWNER:

Name Rudy Walters
Address 694 N. Pacific Highway
Woodburn, Oregon

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted
Dug Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

(5) CASING INSTALLED:

Threaded Welded
12" Diam. from top ft. to 196 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS:

Perforated? Yes No.

Type of perforator used Mills
Size of perforations 7/16 in. by 2 3/4 in.
444 perforations from 120 ft. to 155 ft.
240 perforations from 175 ft. to 195 ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? Yes No If yes, by whom? Driller
Yield: 300 gal./min. with 34 ft. drawdown after 2 hrs.
400 " 44 " same "
" 500 " 57 " same "
Bailer test 600 gal./min. with 71 ft. drawdown after same hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Cement and Puddle Clay
Well sealed from land surface to 20 ft.
Diameter of well bore to bottom of seal 16 in.
Diameter of well bore below seal 12 in.
Number of sacks of cement used in well seal 11 sacks
Number of sacks of bentonite used in well seal sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
Was a drive shoe used? Yes No Plus Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth / strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Marion Driller's well number 1717
NW 1/4 SE 1/4 Section 32 T. 5S R. 1W W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 55 ft.
Static level 1 ft. below land surface. Date 4-21-73
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing

Depth drilled 196 ft. Depth of completed well 196 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Top Soil	0	2	
Yellow Clay	2	47	
Blue Clay	47	55	
Black sand	55	74	
Blue Clay	74	80	
Black sand	80	107	
Blue Clay	107	117	
Black sand and gravel	117	157	
Gray Clay	157	174	
Black sand and gravel	174	196	

Work started 3-23-73 19 Completed 4-21-73 19
Date well drilling machine moved off of well 4-23-73 19

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Ronald W. Morton Date 4-23-73, 19...
(Drilling Machine Operator)

Drilling Machine Operator's License No. 536

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name WILLAMETTE DRILLING COMPANY
(Person, firm or corporation) (Type or print)

Address 7641 35th Ave. NE Salem, Oregon

[Signed] Emil O. Beier
(Water Well Contractor)

Contractor's License No. 2 Date 4-23-73, 19...