NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

1071 STATE OF OREGON

STATE ENGINEER, SALEM, OREGON 97310 ENGINEERse type or print) within 30 days from the 3d ATE ENGINEER SALEM. OREGON OREGON OF WRITE COMPLETED OF WITH STATE ABOVE this line.

State Well No. State Permit No. ...

(1) OWNER:	(10) LOCATION OF WELL:	
Name Kenneth Fessler	County Marion Driller's well number	
Address Rte.2, Box , Woodburn, Oregon	1/4 1/4 Section T.	R. W.M.
	Bearing and distance from section or subdivision	on corner
(2) TYPE OF WORK (check):	OPPROX 700'E +350'S. OF N.W.	
New WellX □ Deepening □ Reconditioning □ Abandon □	T.5 3, RIW.	1.17.01 35.0. 27)
If abandonment, describe material and procedure in Item 12.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed w	
Rotory Cl Driven Cl -		$rox \cdot 40$ ft.
Cable X Jetted Domestic Industrial Municipal	Static level 33 ft. below land s	urface. Date
Dug   □   Bored   □   Irrigation   X   Test Well   □   Other   □	Artesian pressure lbs. per square inch. Date	
CASING INSTALLED: Threaded   Welded \( \bar{\text{b}} \)   Welded \( \bar{\text{b}} \)   Case   Case	(12) WELL LOG: Diameter of well below casing none Depth drilled 142 ft. Depth of completed well 103 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.	
PERFORATIONS: Perforated? \( \sum_{\text{Y}} \) Yes \( \sum_{\text{No.}} \)		
Type of perforator used Mills Knife Perforator	MATERIAL	From To SWL
Size of perforations $\frac{1}{4}$ in. by $3$ in.	Top soil-brn.	0 2
33.0	Sandy loam-brn	2 8
288 perforations from 70 ft. to 94 ft.	Clay sandy-brn	8 30
perforations from ft, to ft.	Clay greyish brn.,gritty-	30 40
	Med.conglom.,brn.,hard-	40 67 (W.B.
(7) SCREENS: Well screen installed? ☐ Yes 💆 No	Sandy clay-brn.,soft-	67 68 <del>2</del>
Manufacturer's Name	Med.conglomgrey-hard-	68₺ 94(W.B
TypeModel No	Sandy clay-dark grey-soft	
Diam, Slot size Set from ft. to ft.	Packed sand & wood-grey	105 106
Diam. Slot size Set from ft. to ft.	Sandy clay-dark grey-soft	106 135
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Clay-grey, sticky, & firm-	135 142
Was a pump test made? A Yes No If yes, by whom?	4	
Yield: 85 gal./min. with ft. drawdown after 5 2 hrs.		
" " "		
" " " "		
Bailer test gal./min. with ft. drawdown after hrs.	·	
Artesian flow g.p.m.		
perature of waterXX Depth artesian flow encountered		
peracure of waterXX Depth artesian now encountered		dMay 1, 1971
(9) CONSTRUCTION:	Date well drilling machine moved off of well	May 1,/1 19
Well seal—Material used Bentocite & puddled clay Well sealed from land surface to 29 ft.	Drilling Machine Operator's Certification: This well was constructed under my	direct supervision.
Diameter of well bore to bottom of sealin.	Materials used and information reported above are true to my best knowledge and belief.	
Diameter of well bore below sealin.	[Signed] Taul X. Stafeli Date 5-28 197/	
Number of sacks of cement used in well sel sacks	(Drilling Machine Operator)	
Number of sacks of bentonite used in will seal sacks	Drilling Machine Operator's License No.	
Brand name of bentonite National	Water Well Contractor's Certification:	
Number of pounds of bentonite per in gallons		
of waterloolbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.	
Was a drive shoe used? A Yes No Plus Size: location ft.	Name R.Stadeli & Sons.Inc.  (Person, firm or corporation) (Type or print)	
Did any strata contain unusable water? Tres 🗷 No	(Person, firm or corporation) (Type or print)	
Type of water? depth, strata	Address Rte. 3, Box 169, Silverton, Oregon	
Method of sealing strata off	[Signed] Jaul J. Statel.	
Was well gravel packed? Yes No Size of gravel: 3/4"rd.	(Water Well Contra	
Gravel placed from	Contractor's License No. 296 Date 5	<u>′28/71</u> , <sub>19</sub>
(USE ADDITIONAL SH	EETS IF NECESSARY)	GD447050 440