ORIGINAL File Original, and FEB 20 1956 Publicate with the	
STATE ENGINEER STATE OF OR SALEM, OREGONTATE ENGINEER	EGONG-3799 Fill In State Permit No.
(1) OWNER: SALEM, OREGON Name Mt. Angel Meat Co.	(10) WELL TESTS: Was a pump test made? ▼ Yes □ No If yes, by whom? Driller
Address Mt. Angel, Ore.	Yield: 70 gal./min. with 106 ft. draw down after 9 hrs.
))))))))))))))))))
(2) LOCATION OF WELL: Albert Ebrer	n n n
County Marion Owner's number, if any—	Artesian flow g.p.m.
R. F. D. or Street No.	Shut-in pressure
Bearing and distance from section or subdivision corner	Temperature of water 52° Was a chemical analysis made? Yes No
1000 ft. North by N. W. of the S. W.	Was electric log made of well? ☐ Yes ⊠No
corner of the S. E. 1 of Section 34 Twp. 5 S. R. 1 W. of the Willamette	(11) THEFT TOC.
Meridian, Marion County, Oregon.	(11) WELL LOG:
(3) TYPE OF WORK (check):	Diameter of well, inches.
well Deepening Reconditioning Abandon	Total depth 405 ft. Depth of completed well 405 ft.
ndonment, describe material and procedure in Item 11.	Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.
PROPOSED USE (check): (5) EQUIPMENT:	Oft. to 60 ft. old well
Domestic M Industrial Municipal Rotary Cable	60 " 64 " Cement gravel
rigation ☐ Test Well ☐ Other ☐ ☐ Dug Well ☐	64 " 153 " Blue clay 153 " 154 " Black sand (fine)
CASING INSTALLED: If gravel packed	153 " 154 " Black sand (fine) 154 " 162 " Dark yellow clay
CASING INSTALLED: If gravel packed □ Welded □ Welded □ □	162 188 " Light blue clay
Gage or Diameter from to	188' 196 " Silt & fine sand (water)
FROM ft. to ft. Diam. Wall of Bore ft. ft.	196" 236 " Blue clay
" 60" 349 " 6" " " " " " " " " " " " " " " " " "	236 to 25 245 Yellow clay
11 11 11 11 11 11 11 11 11 11 11 11 11	245' 258 " Blue clay
11 1) 12 1) 11 11 11 11 11 11 11 11 11 11 11 11	258" 295 " Red clay
31 21 21 31 31 31 31 31 31 31 31 31 31 31 31 31	295, 300 " White clay
Type and size of shoe or well ring Size of gravel:	300" 305 " Yellow clay
Describe joint	305" 343 " Red clay (ocre) 343" 350 " Weathered baselt
(7) PERFORATIONS:	343" 350 " Weathered basalt
Type of perforator used	400" 405 " Lava , brown (water)
SIZE of perforations in., length, by in.	" "
FROM ft. to ft. perf per foot No. of rows	"
n n n n n n n n	n n
))
n n n n n n n n n n n n n n n n n n n	10 19
	" , " " " " " " " " " " " " " " " " " "
SCREENS: Give Manufacturer's Name, Model No. and Size	n n
And a minimum state of a property measure.	21 11
CONSTRUCTION:	n n
Was a surface sanitary seal provided? Tes \(\Bar\) No To what depth ft.	n n
Were any strata sealed against pollution? 🗗 Yes 🗌 No	Ground elevation at well site feet above mean sea level.
If yes, note depth of strata FROM ft, to ft.	Work started Dec. 14 1955, Completed Jan. 31 1956
" Pipe set in rock "	Well Driller's Statement:
	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
METHOD OF SEALING	· ·
(9) WATER LEVELS:	NAME John W. Beck Well Drilling (Person, firm, or corporation) (Typed or printed)
Depth at which water was first found ft.	
Standing level before perforating ft.	Address Rt. 3, Box 45, Canby, Ore.
Standing lever after periorating	Driller's well number 95 356
ng Accepted by:	[Signed] John W Deck
ned] albert but Dated	(Well Driller) License No. 95 Dated Feb. 1 , 19 56
Owner	Jacob, 1956