WATER WELL REPORT STATE OF OREGON



RECEIVED S/1W-35dd

MAR 2 1984

State Permit No.	***************************************
DED*	

			State Per
E TYPE	or WATER	TRESOURCES	DEPT.

(1) OWNER:	(10) LOCATION OF WELL:	
Name Hammelman Brothers	County Marion Driller's well number	
Address 9495 Meridian Rd.	SE 4 SE 4 Section 35 T. 5S R. 1W	W.M.
City Mt. Angel State Or.	Tax Lot # Lot Blk Subdivision	
(2) TYPE OF WORK (check):	Address at well location: NA	
New Well □ Deepening X Reconditioning □ Abandon □		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 536	fţ.
- v	Static level ft. below land surface. Date 2-	<u>17-</u> 8
Freery Mud Dug Irrigation X Test Well Other	Artesian pressure lbs. per square inch. Date	
Bored Thermal: Withdrawal Reinjection	(12) WELL LOG: Diameter of well below casing 7.7/8	
(5) CASING INSTALLED: Steel	Depth drilled 585 ft. Depth of completed well 585 Formation: Describe color, texture, grain size and structure of materials; and	ft. d show
"Diam. from	thickness and nature of each stratum and aquifer penetrated, with at least one for each change of formation. Report each change in position of Static Water and indicate principal water-bearing strata.	entry Level
LINER INSTALLED: none		
		WL
	Basalt hard grey 499 530 Basalt porous blk 530 540 Hz	
(6) PERFORATIONS: Perforated? ☐ Yes X No		<u> 20</u>
Type of perforator used		
Size of perforations in. by in.		
perforations from ft. to ft.		
perforations from ft. to ft.	Basalt hard, visic. blk 567 585 Hz	<u>:U</u>
perforations from ft. to ft.		
(7) SCREENS: Well screen installed? ☐ Yes 🗖 No		
Manufacturer's Name		
Type Model No.		
Diam. Slot Size	:	
Diam. Slot Size Set from ft. to ft.		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
a pump test made? Yes X No If yes, by whom?	No. of the state o	
rield: gal/min. with ft. drawdown after hrs.		
II " " "		
Air test 600 gal./min. with drill stem at 585 ft. 1 hrs.		
Bailer test gal./min. with ft. drawdown after hrs.		
esian flow g.p.m.		
remperature of water Depth artesian flow encountered ft.	Work started 2-16 19_84 Completed 2-17	- 01
(9) CONSTRUCTION: Special standards: Yes □ NoX		19 84 19 84
Well seal—Material used Original	(unbonded) Water Well Constructor Certification (if applicab	
Well sealed from land surface to ft.	This well was constructed under my direct supervision. Materials	le):
Diameter of well bore to bottom of sealin.	and information reported above are true to my best knowledge and be	elief.
Diameter of well bore below sealin.	[Signed] Date, 19	
Number of sacks of cement used in well seal sacks	Bonded Water Well Constructor Certification:	
How was cement grout placed?	Bond Issued by Union Indemnity	
The state of the s	(number) Surety Company Name	
w no m up p.v.	This well was drilled under my jurisdiction and this report is tr the best of my knowledge and belief.	ue to
Was a drive shoe used? ☐ Yes ☐ Mo Plugs Size: location ft.	Name West Coast Drilling (Type or prin	
Was a drive shoe used? ☐ Yes ☐ Yes ☐ Plugs Size: location ft. Did any strata contain unusable water? ☐ Yes ☒ No	Address 220 Academy St. Mt. Angel, Or.	t)
Type of Water? depth of strata		
Method of sealing strata off	[Signed] hunfullan Wall Comment	
Was well gravel packed? ☐ Yes X No = Size of gravel:	Water Well Constructor Date 2-21 198	8LL
Gravel placed from	, 199	ਜਜ ਾ