

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

MARI 2207 WATER WELL REPORT

MARI 2207

AUG 29 1967

STATE OF OREGON

State Well No. 5/2w-1 A

STATE ENGINEER, SALEM, OREGON 97310

within 30 days from the date of well completion.

STATE ENGINEER OREGON

(Please type or print)

(Do not write above this line)

State Permit No.

(1) OWNER: Ralph Wurdinger

Name Address Rt 1 Box 258 Woodburn, Oreg.

(2) TYPE OF WORK (check):

New Well [x] Deepening [] Reconditioning [] Abandon []

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [x] Cable [] Dug [] Driven [] Jetted [] Bored []

(4) PROPOSED USE (check):

Domestic [] Industrial [] Municipal [] Irrigation [x] Test Well [] Other []

CASING INSTALLED:

6" Diam. from 0 ft. to 20 ft. Gage 250
10" Diam. from 1 ft. to 154 ft. Gage 250

PERFORATIONS:

Perforated? [x] Yes [] No

Type of perforator used torch
Size of perforations 1/8 in. by 12 in.
360 perforations from 0 ft. to 20 ft.
400 perforations from 1 ft. to 154 ft.

(7) SCREENS:

Well screen installed? [] Yes [x] No

Manufacturer's Name Type Model No.
Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.

Static level 25 ft. below land surface Date 5/8/67
Artesian pressure lbs. per square inch Date

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? [x] Yes [] No If yes, by whom? Driller
500 gal./min. with 60 ft. drawdown after 3 hrs.
Baller test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m. Date
Temperature of water Was a chemical analysis made? [] Yes [] No

(10) CONSTRUCTION: cement

Well seal—Material used cement
Depth of seal 20 ft.
Diameter of well bore to bottom of seal 28 in.
Were any loose strata cemented off? [] Yes [x] No Depth
Was a drive shoe used? [] Yes [x] No
Did any strata contain unusable water? [] Yes [x] No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? [x] Yes [] No Size of gravel: 3/8"
Gravel placed from 0 ft. to 154 ft.

(11) LOCATION OF WELL:

County Marion Driller's well number
Bearing and distance from section or subdivision corner
800 ft S & 400 ft W of N.E. Cor sec 1
T. 5. S, R 2 W.

(12) WELL LOG:

Diameter of well below casing 20" surface 18"
Depth drilled 154 ft. Depth of completed well 148 ft.
6" cement plug
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

Table with columns: MATERIAL, From, To, SWL. Rows include Top soil brn, Clay brn, Fine sand brn, Clay brn, Med. sand some fine blk., gravel W.B., Course Sand & gravel blk., Clay brn, Course sand small, gravel W.B.

Work started 4/27/67 1967 Completed 5/8 1967
Date well drilling machine moved off of well 5/8 1967

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] C. E. Stadel Date 7/12, 1967. (Drilling Machine Operator)

Drilling Machine Operator's License No. 84

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME R. Stadel & Sons (Person, firm or corporation) (Type or print)
Address Rt 3 Box 169, Silverton, Oreg.
[Signed] Paul R. Stadel (Water Well Contractor)
Contractor's License No. 296 Date 7/12 1967