

The original and first copy of this report are to be filed with the

WATER WELL REPORT

RECEIVED

STATE OF OREGON

MARI... 2208

State Well No. 55/2W-1 DA

ENGINEER, SALEM, OREGON 97301

within 30 days from the date of well completion.

AUG 12 1977

(1) OWNER:

WATER RESOURCES DEPT.

Name Skylane Farms SALEM, OREGON

Address Route 1, Box 503 AA Woodburn, Oregon 97071

(2) TYPE OF WORK (check):

New Well X Deepening Reconditioning Abandon

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary X Driven Cable Jettied Dug Bored

(4) PROPOSED USE (check):

Domestic X Industrial Municipal Irrigation Test Well Other

CASING INSTALLED:

6" Diam. from 8" to 27.7" Gage .250
6" Diam. from 28" to 245.4" Gage .250
10" Diam. from 32" to 246.1" Gage .279

Gravel Feed PERFORATIONS:

Perforated? XX Yes No

Type of perforator used torch
Size of perforations 3/8 in. by 6 in.
6" - 342 perforations from 174.3" to 234.4"
10" - 570 perforations from 175.6" to 235.2"

(7) SCREENS:

Well screen installed? Yes No

Manufacturer's Name Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

airlift
Was test made? X Yes No If yes, by whom? driller
Yield: 600 gal./min. with 36 ft. drawdown after 2 hrs.
458 " 32 " 4 "
Baller test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used cement
Well sealed from land surface to 25 ft.
Diameter of well bore to bottom of seal 24 in.
Diameter of well bore below seal 24 in.
Number of sacks of cement used in well seal 36
Number of sacks of bentonite used in well seal
Brand name of bentonite
Number of pounds of bentonite per 100 gallons of water
Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water depth of strata
Method of sealing strata off
Was well gravel packed? X Yes No Size of gravel: 3/4 - 1/2"
Gravel placed from 25 ft to bottom ft.

(10) LOCATION OF WELL:

County Marion Driller's well number 7714
NE 1/4 NW 1/4 Section 1 T. 58 R. 2W W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found ft.
Static level 48 ft. below land surface. Date 7/19/77
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 8" - 243"
Depth drilled 243 ft. Depth of completed well 10" - 238"
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with columns: MATERIAL, From, To, SWL. Content: See attached sheet

Work started 5/10 1977 Completed 7/26 1977
Date well drilling machine moved off of well 7/26 1977

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Donald S. Davis Date 8/9, 1977
(Drilling Machine Operator)

Drilling Machine Operator's License No. 1085

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name Schneider Equipment, Inc.
Address Star Route Box 97, St. Paul 97137
[Signed] Stephen J. Schneider
Contractor's License No. 649 Date 8/9, 1977