NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the data AUG 17 1966

WHO IS TO THE OF OREGON 197310 within 30 days from the data AUG 17 1966

State Well No. 5

State Permit No.

1) OWNER: STATE ENGINEER	(11) WELL TESTS: Drawdown is amount we lowered below static lev	rel	21 12
Name Corbett Holt	Was a pump test made? 🖸 Yes 🗌 No If yes, by whom	? dri	<u>ller</u>
Address	Yield: 40 gal./min. with 25 ft. drawdow	n after	4 hrs
Woodburn, Oregon	" " " " " " " " " " " " " " " " " " "		
2) LOCATION OF WELL:	" " "		"
County Marian Driller's well number	Bailer test gal./min. with ft. drawdo	wn after	hrs
A EG OW	Artesian flow g.p.m. Date		
A Section I. Section	Temperature of water Was a chemical analysis m	nade? 🔲 🏾	Yes 👿 N
Bearing and distance from section or subdivision corner	(12) WELL LOG: Diameter of well below cas	sing	
AARAS PERCENTAGE		_	
	Depth drilled 137 ft. Depth of completed well		37 ft
	Formation: Describe by color, character, size of material show thickness of aquifers and the kind and nature of the stratum penetrated, with at least one entry for each ch	ana stru he materi	cture, and ial in each
The state of the s	stratum penetrated, with at least one entry for each ch	ange of	formation
	MATERIAL	FROM	TO
(3) TYPE OF WORK (check):	Soil	0	3
Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐	Brown sandy clay	3	29
andonment, describe material and procedure in Item 12.	Blue sandy clay	29	105
(4) PROPOSED USE (check): (5) TYPE OF WELL:	Sand	105	127
Potenty Cl. Driven Cl.	Broken gravel	127	132
Domestic M industrial Municipal Coble 50 Jetted	Sand	132	135
irrigation   Test Well   Other   Cable & Setted   Dug   Bored	Gravel	175	
(2) 20 20 20 20 20 20 20 20 20 20 20 20 20	Clay	136	136
		טעב	137_
6			
"Diam. from ft. to ft. Gage		1	
"Dlam. fromft. toft. Gage			
(7) PERFORATIONS: Perforated? ★ Yes □ No			
Type of perforator used Millknife			
Size of perforations 3/8 in. by 2 in.			
8 perforations from ft. to ft.			
perforations fromft. toft.			
perforations fromft. toft.			
perforations from ft. to ft.		<b>  </b>	
(8) SCREENS: Well screen installed?   Yes No			
Manufacturer's Name		<u> </u>	
Model No.			
Dram Slot size Set from ft. to ft.			<del></del>
Diam. Slot size Set from ft. to ft.	Work started August 9 1966 Completed Aug		
(0) CONCEDICATON.		rust 1	1 19 6
(9) CONSTRUCTION:	(13) PUMP:		
Well seal—Material used in sealPuddled Mud	Manufacturer's Name		
Depth of seal 18 ft. Was a packer used?no	Туре:		
Diameter of well bore to bottom of sealin.	- T		
Were any loose strata cemented off? [ Yes No Depth	Water Well Contractor's Certification:		
Was a drive shoe used?  Yes XNo	This well was drilled under my jurisdiction a	nd this	report fo
Was well gravel packed? ☐ Yes ☒ No Size of gravel;	true to the best of my knowledge and belief.	na tins	report 1
Gravel placed fromft.	NAMES John States		
Did any strata contain unusable water \( \begin{align*} \text{Yes} \text{X} \end{align*} \text{No} \end{align*}	NAME John Truman Miller (Ferson, firm or corporation) (Typ	e or print)	······································
Type of water? depth of strata		gon	
		.74	
Method of sealing strata off	Drilling Machine Operator's License No. 26		
(10) WATER LEVELS:	Island Valendi his M	,	
Static level 35 ft. below land surface Date 8/11/66	[Signed] (Water Well Contractor)	<i></i>	
Artesian pressure   lbs. per square inch Date	Comment 277 - Anonet	: 13	., 66
(USE A DOUBLOWAY OF	Contractor's License No DateDate		, 19