NOTICE TO WATER WELL CONTRA

The original and first cool
of this report are to be
filed with the

JUL 21 1965WATER WELL REPORT

State Well No.

STATE ENGINEER, SALEM, ORGON Within 30 days from the date SALEM OF CONTROL OF Well completion.

G-3559

State Permit No.

SALEM ORFGON	- 433 (
(1) OWNER:	(11) WELL TESTS: Drawdown is amount to lowered below static levels.	water level is
Name NORMAN WILSON	Was a pump test made? Yes \(\subseteq \) No If yes, by whom	
Address RT. I BOX 349	Yield: 500 gal./min. with 15 ft. drawdow	
HUBBARD, OREGON	" 600 " 24 "	29 "
(2) LOCATION OF WELL:	" 7 50 " 28 "	29 "
MADTON	Bailer test gal./min. with ft. drawdo	wn after hrs.
Z A E C OW	Artesian flow g.p.m. Date	
34 34 Section 3-4 T. 5 S R. 2W W.M.	Temperature of water Was a chemical analysis n	nade? 🗆 Yes 🔲 No
Bearing and distance from section or subdivision corner	(12) WELL LOG: Diameter of well below car	zing
Equation 1.	_	
	Depth drilled I40 ft. Depth of completed wel	
	Formation: Describe by color, character, size of material show thickness of aguifers and the kind and nature of t stratum penetrated, with at least one entry for each ch	and structure, and he material in each
	stratum penetratea, with at least one entry for each cr	lange of formation.
(2) TVDE OF WORK (check).	MATERIAL	FROM TO
(3) TYPE OF WORK (check):	TOP SOIL	0 5
New Well Deepening Reconditioning Abandon	CLAY	5 25
iandonment, describe material and procedure in Item 12.	SAND	25 50
(4) PROPOSED USE (check): (5) TYPE OF WELL:	CLAY	50 58
Domestic Industrial Municipal Rotary Driven	SAND	58 65
Irrigation Test Well Other Cable Jetted	CLAY	65 85
Dug Bored	SAND	85 95
(6) CASING INSTALLED: Threaded Welded	CLAY	95 IO5
IZ Diam. from TOP ft. to I40 ft. Gage 250	SAND	I05 I20
" Diam. from ft. to ft. Gage	GRAVEL SAND	180 I55
"Diam. fromft. Gage	DALID	135 140
(7) PERFORATIONS: Perforated? Yes No		
Type of perforator used MTLLS		
Size of perforations in. by 2 in.		· · ·
		*
perforations from 120 ft. to 135 ft. perforations from 120 ft. to 155 ft.		
perforations fromft. toft.		
perforations from ft. to ft.		
perforations from ft. to ft.		
(8) SCREENS: Well screen installed? Yes No		
Manufacturer's Name Model No.	-	
Slot size Set from ft. to ft.	Trop do to the control of the contro	·
Diam. Slot size Set from ft. to ft.		Y 12 1965
	Date well drilling machine moved off of well JULY	TS T8628
(9) CONSTRUCTION:	(13) PUMP:	
Well seal-Material used in seal CENT & PUDDLE CLAY	Manufacturer's Name	
Depth of sealft. Was a packer used?	Type:HP	
Diameter of well bore to bottom of sealin.	Woton Woll Control of the Control of	
Were any loose strata cemented off? Tyes No Depth	Water Well Contractor's Certification:	
Was a drive shoe used? ▼Yes □ No	This well was drilled under my jurisdiction a	nd this report is
Was well gravel packed? ☐ Yes ♣No — fize of gravel:	true to the best of my knowledge and belief.	•
Gravel placed from ft. to ft.	NAME WILLAMETTE DRILLING CO	
Did any strata contain unusable water? Yes 🗆 No	(Person, firm or corporation) (Typ.	e or print)
Type of water? depth of strata	Address RT. 2 BOX 276 SALEM, O	REGON
Method of sealing strata off	Drilling Machine Operator's License No	
(10) WATER LEVELS:	FIDD P	
Static level 20 ft. below land surface Date 7/12/65	[Signed] (Mater Well Contractor)	
Tugra inch Data	Contractor's License No. 2 Date JULY I	2 TORK
Artesian pressure lbs. per state men Date	Date - Date	<u></u>

(USE ADDITIONAL SHEETS IF NECESSARY)