	2315		
NOTICE TO WATER WELL CONTRACTOR E G E I VE D  The original and first copy of this report are to be filed with the  AUG 10 1WATER WE	LL REPORT 5	, Q 42-	-3 R
STATE ENGINEER, SALEM, OREGON TO SALEM. OREGON	State Well No		
(1) OWNER:	(11) WELL TESTS: Drawdown is amount or lowered below static le	water leve	el is
Name Horst P Raustein	Was a pump test made? Fyes \( \Bar{\text{No}}\) No If yes, by whom? driller		
Address Rte Box 471	Yield: 120 gal./min. with 40 ft. drawdow		4 hrs.
Woodburn, Oregon	<u>" 170 " 69 "</u>		4 "
(2) LOCATION OF WELL:	" "		"
75	Bailer test gal./min. with ft. drawdo	wn after	hrs.
County Marian Driller's well number  14 14 Section 3 T. 5S R. 2W W.M.	Artesian flow g.p.m. Date		
14 14 Section 3 T. 58 R. 2W W.M.  Bearing and distance from section or subdivision corner	Temperature of water Was a chemical analysis r	nade? 🔲 🥇	les 🗶 No
bearing and distance from section or subdivision corner	(12) WELL LOG: Diameter of well below ca	sing	**************************************
The second secon	Depth drilled 130 ft. Depth of completed wel	ո 1	.30 ft.
· ·	Formation: Describe by color, character, size of materia show thickness of aguifers and the kind and nature of t stratum penetrated, with at least one entry for each cl	he materi hange of	al in each formation.
(3) TYPE OF WORK (check):	MATERIAL	FROM	TO TO
New Well Deepening Reconditioning Abandon	Soil	0	
In andonment, describe material and procedure in Item 12.	Brown sandy clay	7.0	<u> 19</u>
	Blue sandy clay	19	64
(4) PROPOSED USE (check): (5) TYPE OF WELL:	Grey clay	64	81
Domestic   Industrial   Municipal   Rotary   Driven   Gable   Cable	Broken sand and gravel Clay	81	102
Irrigation  ☐ Test Well ☐ Other ☐ Dug ☐ Bored ☐	Sand	102	<u>103</u> 106'6'
(4) 414714 714714	Broken gravel	106 6 6 1	
9 0 170 1/4	Sand	118	121
	Gravel	121	_130_
		1	
	· · · · · · · · · · · · · · · · · · ·		<del></del>
(7) PERFORATIONS: Perforated? Tyes   No			
Type of perforator used Millknife			
Size of perforations         3/8         in. by         3         in.           56         perforations from         125         ft. to         127         6"ft.			
perforations from ft. to ft.			
perforations fromft. toft.		<u> </u>	
perforations fromft. toft.		<del>                                     </del>	
perforations from ft. to ft.		<u> </u>	<del> </del>
(8) SCREENS: Well screen installed?   Yes  No			-
Manufacturer's Name	-		<del></del>
Model No.		i1	
Diam. Slot size Set from ft. to ft.	Work started August 3 1966 Completed At	igust	9 19 66
Diam. Slot size Set from ft. to ft.		igust	
(9) CONSTRUCTION:	(13) PUMP:		
Well seal—Material used in seal Puddled Mud	Manufacturer's Name		
Depth of sealft. Was a packer used?	Type:		
Diameter of well bore to bottom of sealin.	Water Well Contractor's Certification:		
Were any loose strata cemented off? Tes 🗷 No Depth	water wen Contractor's Certification:		
Was a drive shoe used? ☐ Yes INo	This well was drilled under my jurisdiction a true to the best of my knowledge and belief.	ind this	report is
Gravel placed from ft. to ft.	NAME John Truman Miller (Person, firm or corporation) (Type or print)		
Did any strata contain unusable water? Yes 🖪 No			
Type of water? depth of strata	Address P O Box 42 Hubbard, Oregon		
Method of sealing strata off	Drilling Machine Operator's License No26		
(10) WATER LEVELS:	The state of the s		
Static level 31 ft. below sand surface Date 8/9/66	(Water Well Contractor)	_	
Artesian pressure lbs. per square inch Date	Contractor's License No. 277 Date August	; 9	., 196 <b>6</b>

(USE ADDITIONAL SHEETS IF NECESSARY)