

RECEIVED

MARI. 2338

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM 10, OREGON within 30 days from the date of well completion.

OCT 4 1962 WATER WELL REPORT STATE OF OREGON (Please type or print)

State Well No. 5/2W-6D1
State Permit No.

(1) OWNER:

Name Oregon State Game Comm
Address Rt 18 Box 325 Corvallis

(2) LOCATION OF WELL:

County Marion Driller's well number
Bearing and distance from section or subdivision corner T 58. R 2W Sec 6

(3) TYPE OF WORK (check):

New Well [X] Deepening [] Reconditioning [] Abandon []
Abandonment, describe material and procedure in Item 12.

(4) PROPOSED USE (check):

Domestic [] Industrial [] Municipal []
Irrigation [] Test Well [X] Other [X]

(5) TYPE OF WELL:

Rotary [] Driven []
Cable [X] Jetted []
Dug [] Bored []

(6) CASING INSTALLED:

12" Diam. from 7.5 ft. to 200 ft. Gage 5/6
Threaded [] Welded [X]

(7) PERFORATIONS:

Perforated? [X] Yes [] No
Type of perforator used touch
Size of perforations 3/8 in. by 6 in.
650 perforations from 60 ft. to 205 ft.

(8) SCREENS:

Well screen installed [] Yes [X] No
Manufacturer's Name
Diam. Slot size Set from ft. to ft.

(9) CONSTRUCTION:

Well seal—Material used in seal cement
Depth of seal 18 ft. Was a packer used? yes
Diameter of well bore to bottom of seal 20 in.
Were any loose strata cemented off? [] Yes [X] No Depth
Was a drive shoe used? [] Yes [X] No
Was well gravel packed? [X] Yes [] No Sp. of gravel: 3/8 pea
Gravel placed from 18 ft. to 200 ft.
Did any strata contain unusable water? [] Yes [X] No
Type of water? Depth of strata
Method of sealing strata off

(10) WATER LEVELS:

Static level 50 ft. below land surface Date 10/2/62
Artesian pressure lbs. per square inch Date

(11) WELL TESTS:

Drawdown is amount water level is lowered below static level
Was a pump test made? [X] Yes [] No If yes, by whom? Driller
Yield: 380 gal./min. with 35 ft. drawdown after 6 hrs.
425 " 37 " 6 "
460 " 45 " 6 "
Bailer 150 gal./min. with 18 ft. drawdown after 6 hrs.
Artesian flow g.p.m. Date
Temperature of water 58 Was a chemical analysis made? [] Yes [X] No

(12) WELL LOG:

Diameter of well below casing -
Depth drilled 200 ft. Depth of completed well 200 ft.
Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.

Table with columns MATERIAL, FROM, TO. Rows include Grey Clay (0-5), Brown Clay (5-40), Blue Clay (40-55), Black Sand (55-60), Blue Sandy Clay (60-70), Blue Clay (70-85), Black Sand & gravel (85-100), Sand & stone (100-101), Blue Clay (101-152), Grey Rock (152-155), Light Blue Clay (155-160), Blue Clay (160-185), Hard packed sand (185-200).

Work started 9/24 1962 Completed 10/2 1962
Date well drilling machine moved off of well 10/2 1962

(13) PUMP:

Manufacturer's Name
Type: H.P.

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME H. H. Row Drilling & Supplies
Address 729 N Main Newberg, Ore
Drilling Machine Operator's License No. 87
[Signed] Paulie M. Bluffino (Water Well Contractor)
Contractor's License No. 117 Date 10/2 1962