MARIE NOTICE TO WATER WELL CONTRACTOR JUN - 7 1963 STATE OF OREGON The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM 10, OREGON within 30 days from the dated 17 (Please type or print) of well completion. State Permit No. Drawdown is amount water level is lowered below static level (1) OWNER: (11) WELL TESTS: Philip Wolf, Jr. Was a pump test made? 🗌 Yes Name No If yes, by whom? Rt. 1, Box 295, Gervais, Ore. Yield: 1700 gal./min. with 92 Address ft. drawdown after 1500 84 (2) LOCATION OF WELL: gal./min. with Bailer test ft. drawdown after hrs. County Marion Driller's well number Artesian flow g.p.m. Date 6 or 7_{T.} 55 R. 2W 14 Section Temperature of water Was a chemical analysis made? ☐ Yes ☐ No Bearing and distance from section or subdivision corner app 2500 feet West of other well (12) WELL LOG: Diameter of well below casing ... Depth drilled 151 8 ft. Depth of completed well Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation. MATERIAL FROM ጥጋ Top soil (3) TYPE OF WORK (check): Brown clay 3 14 New Well 🔀 Deepening [Reconditioning [Abandon | bandonment, describe material and procedure in Item 12. Brown sandy clay Grey clay 79 19 35 (5) TYPE OF WELL: (4) PROPOSED USE (check): Hard grev clav 35 37 Rotary X Driven Domestic | Industrial | Municipal | Grey clay 37 56 Cable Jetted Irrigation ☐ Test Well ☐ Other ☐ Blue clay Dug Bored Black sand 64. (6) CASING INSTALLED: Threaded ☐ Welded ☑ Brown clay 72 73 18 " Diam. from 0 ft. to 20 ft. Gage 250 Milk colored clay (white) 73 12 "Diam from 0 ft to 156'8" ft. Gage .250 Chocolate clay 97 ft. to tt. Gage Soft brown clay 97 100 Brown clay & sand layer Perforated? 🖫 Yes 🗌 No COL (7) PERFORATIONS: 106 Green sand 106 torch 108 Type of perforator used Blue clay Sand & Brown clay layers perforations 5/16 in. by 8 in. 96 perforations from 68 8 1 ft. to 76 8 1 108 Size of perforations 5/16 114 114 120 Light colored clay (white) 660 perforations from 9618! ft. to 151'8" 120 127 Blue clay 127 perforations from 135 Coarse black sand 135 perforations from Brown clay 152 156 ft. to perforations from Well screen installed (8) SCREENS: Manufacturer's Name Model No. n. Slot size Set from ft. to Work started 4-15 19 63 Completed 19 63 5-10 ___ Set from ____ ft. to ____ Date well drilling machine moved off of well 19 63 Drilled 24" hole (9) CONSTRUCTION: (13) PUMP: Well seal-Material used in seal _____concrete Manufacturer's Name Diameter of well bore to bottom of seal 24 in. Were any loose strata cemented off? Yes H No Depth Water Well Contractor's Certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Was a drive shoe used? ☐ Yes K No Was well gravel packed? X Yes No Si of gravel: 3/4 - 1/2 Gravel placed from 0 ft. to 156 Milo Schneider NAME (Person, firm or corporation) Did any strata contain unusable water TYes A No (Type or print) Star Rt., Box 97, St. Paul, Oregon Depth of strata Type of water? Method of sealing strata off Drilling Machine Operator's License No. (10) WATER LEVELS: ft. below land surface Date 5-8-63 Static level (Water Well Contractor) Contractor's License No. 387 Date 5-10 , 19.63 lbs. per square inch Date Artesian pressure

(USE ADDITIONAL SHEETS IF NECESSARY)