ÅPR **2 4** 1975 filed with the State Well No. 5 - STATE OF OREGON Thease type or print) STATE ENGINEER State Permit No. STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date Do not write above this line ALEM. OREGON of well completion. (10) LOCATION OF WELL: (1) OWNER: 7417 Robert Schmidt Marion County Driller's well number Name Rt. 1. Box 466 Woodburn, Ore. 97071 Bearing and distance from section or subdivision corner (2) TYPE OF WORK (check): New Well Deepening [ Reconditioning [ Abandon [7] If abandonment, describe material and procedure in Item 12. (11) WATER LEVEL: Completed well. (3) TYPE OF WELL: (4) PROPOSED USE (check): Depth at which water was first found RevRotary Driven 🗆 Static level 15 Domestic | Industrial | Municipal | ft. below land surface. Cable Jetted | Irrigation Test Well | Other Dug Bored | Artesian pressure lbs, per square inch. Date CASING INSTALLED: (12) WELL LOG: Diameter of well below casing 131'8" ft. to ." Diam, from .. Depth drilled 245 ft. Depth of completed well 244'10'ft. "Diam. from 151'8" t. to ... ..." Diam. from . Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, 171'10 with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata. PERFORATIONS: Perforated? X Yes No. Type of perforator used MATERIAL Size of perforations See sheet attached Gage 320 Diam. from 232'10" to 244'1 perforations from . Diam. from 1'6" 7017 perforations from perforations from (7) SCREENS: Well screen installed? | Yes | No Manufacturer's Name ..... Set from .. Diam. \_\_\_\_ Slot size \_\_\_\_ Set from . Drawdown is amount water level is lowered below static level (8) WELL TESTS: Was a pump test made? 

Yes □ No If yes, by whom? ft. drawdown after gal./min. with hrs, ft. drawdown after Bailer test gal./min. with hrs. Artesian flow Depth arfesign flow encountered ..... 11-4-Completed 4-8 erature of water Date well drilling machine moved off of well 4-8 (9) CONSTRUCTION: pressure grouted zonolite and cement Drilling Machine Operator's Certification: This well was constructed under my direct supervision. Well sealed from land surface to Materials used and information reported above are true to my Diameter of well bore to bottom of sea best knowledge and belief Diameter of well bore below seal .. Number of sacks of cement used in well seal ... Drilling Machine Operator's License No. .... Number of sacks of bentonite used in well seal Brand name of bentonite Water Well Contractor's Certification: Number of pounds of bentonite per 100 gallons This well was drilled under my jurisdiction and this report is ....lbs./100 gals. true to the best of my knowledge and belief. Was a drive shoe used? Yes No Plus ..... Size: location . Name Milo Schneider Equipment Co. Did any strata contain unusable water Yes Yes No (Person, firm or corporation) Address Star Rt., Type of water? Method of sealing strata off Was well gravel packed? Yes No Size of gravel: 3/4 bottom Contractor's License No. 387 Date 4-15 Gravel placed from (USE ADDITIONAL SHEETS IF NECESSARY)

WATER WELL REPOR

NOTICE TO WATER WELL CONTRACTOR The original and first copy >

of this report are to be

					NHOS OTH	SCHNEIDER EQ	LNEWHINDS				U TOTAL STATE OF THE PARTY OF T	1. + 1. miles	
					T PAUL O	NOON !	H 633-26	18 A		がする			
				7	JAN A	Track.	2000	X					
											11-1		
11.													
									الله الله				
, o	16.43	7											
	1												
n di Mark													
}													
100													
्यार् देवकाते इ									100				
) )													
* do													
104			A						2				
* 6				1									
		+		37						計 え			
						2				7			
						3				m			
				P						10			
										1			
7				汉		200				30			
Ā										36			
													と

## Robert Schmidt #7417

Material	From	To
Top soil Brown clay Gray soft clay Gray clay Black sand Gravel (2") Gray clay Black sand & gravel (2") Wood gray clay Black sand & gravel (2") Black sand Blue clay Gray sandy clay (dry) Black sand Gray clay Cemented black sand Brown clay Cemented black sand Gray clay Cemented black sand Gray clay	0 3 12 65 70 99 101 117 125 140 146 157 169 177 185 194 198 203 233 239 241 242	3 12 65 70 99 101 117 128 140 146 157 169 172 177 1854 198 203 233 233 241 242 245