## NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 973 within 30 days from the date of well completion.

SINEER REPORT

State Permit No. ....

STATE ENGINEER			
OWNER: SALLM ORGON (11) LOCATION OF WELL:			
Name Harald Ingram	County Marian Driller's well nu		
Address Hubbard, Oregon	14 14 Section 2 T. 45	R. 1W	W.M.
	Bearing and distance from section or subdivision	1 corner	
(2) TYPE OF WORK (check):			
New Well Deepening Reconditioning Abandon			
If abandonment, describe material and procedure in Item 12.			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(12) WELL LOG: Diameter of well b	elow casing	
Rotary   Driven   Domestic   Industrial   Municipal	Depth drilled 178 ft. Depth of comple	eted well 1	78 ft.
Dug ☐ Bored ☐ Irrigation ■ Test Well ☐ Other ☐	Formation: Describe color, texture, grain size	and structure of	materials;
CASING INSTALLED: Threaded   Welded	and show thickness and nature of each stratu- with at least one entry for each change of form	m and aquifer pe ation, Report eac	enetrated, ch change
8 " Diam. from 0 ft. to 178 ft. Gage 14"	in position of Static Water Level as drilling pro	ceeds. Note drill	ing rates.
" Diam. from ft. to ft. Gage	MATERIAL	From To	SWL
" Diam. from ft. to ft. Gage	Soil	0 2	
DEDEOD ATIONS.	Brewn sandy clay	2 51	
PERFORATIONS: Perforated? W Yes \( \square\) No.	Blue sandy clay	51 74	<del> </del>
Type of perforator used Millknife  Size of perforations 3/8 in. by 2½ in.	Brewn sand	74 86	4
	Blue clay	86 113	
96 perforations from 167 ft. to 172 ft.	Sand	113 122	
perforations from ft. to ft.	Breken sand & gravel	122 126	,
perforations from ft. to ft	Blue clay	126 149 149 156	' 1
perforations from ft. to ft.	Sand	T - 'J   'J	31611
perforations from	Sand & gravel	58'6" 166	
(7) SCREENS: Well screen installed?   Yes No	Gravel	166 17	-
Manufacturer's Name	Blue clay	175 178	
Type Model No.			
Diam. Slot size Set from ft. to ft.		<del>                                     </del>	
Diam. Slot size Set from ft. to ft.			-
(8) WATER LEVEL: Completed well.			
tic level 57 ft. below land surface Date $7/8/68$		+	
sian pressure lbs. per square inch Date			
(9) WELL TESTS: Drawdown is amount water level is lowered below static level			
TOWCICA DOLON DIAMO 15 TO			
Was a pump test made? 🗷 Yes 🗆 No If yes, by whom? driller	Work started June 28 1968 Comple	ted July 8	19 68
d: 200 gal./min. with 43 ft. drawdown after 2 hrs.	Date well drilling machine moved off of well	July 8	19 68
" " "		,	
" " " " " " " " " " " " " " " " " " "	Drilling Machine Operator's Certification: This well was constructed under my o	lirect supervisio	n. Mate-
Bailer test gal./min. with ft. drawdown after hrs.	rials used and information reported about knowledge and belief.	ove are true to	my best
Artesian flow g.p.m. Date	John Mille	Date July	8 1068
Temperature of water Was a chemical analysis made?   Yes   No	[Signed]	. Date www.	, тамм.
(10) CONSTRUCTION:	Drilling Machine Operator's License No.	26	
Well seal—Material used Puddled mud	Drining Machine Operator's Dicense Ivo.		
Depth of seal	Water Well Contractor's Certification:		
Diameter of well bore to bottom of seal	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
Were any loose strata cemented off?  Yes No Depth	John Mauman Miller		
Was a drive shoe used?   Yes   No	NAME (Person, firm or corporation)	(Type or pri	nt)
Did any strata contain unusable water? 🗌 Yes 🙀 No	Address P O Bex 42 Hubba	rd, Oregon	
Type of water? depth of strata	1 17 17 011	,	
Method of sealing strata off	[Signed] AM N Mulle	✓	
Was well gravel packed?   Yes No Size of gravel:	(Water Well Contr		
Gravel placed from ft. to ft.	Contractor's License No277 Date	July 8	, 1958