ORIGINAL WATER W	ELL REPORT State Well No	6865/2W-
File Original and 1 0 1957  Duplicate with the 1 0 1957  STATE OF	OF OREGON State Permit No.	594
(1) OUNTEN. OREGON Name Lee Terry	(11) WELL TESTS: Drawdown is amount v lowered below static let.  Was a pump test made? ∑ Yes ☐ No If yes, by whom	vel
Address Woodburn, Ore.	Yield:         112         gal./min. with         30         ft. drawdow           "         150         "         44         "	
(2) LOCATION OF WELL: County Well Owner's number, if any	Bailer test gal./min. with ft. drawdow.	n after hi
W.M. Section 3 T. 5 S. R. 2 W.M. Bearing and distance from section or subdivision corner	Artesian flow g.p.m. Date Temperature of water 52 Was a chemical analysis ma	ide? 🗌 Yes 🔀 1
he come of most mortherly M.W.	(12) WELL LOG: Diameter of well Depth drilled 230 ft. Depth of completed w	070
one of the Peter Raymond D. F. C.	Formation: Describe by color, character, size of materia show thickness of aquifers and the kind and nature of stratum penetrated, with at least one entry for each c	l and structure, ar the material in each ange of formatio
	MATERIAL	FROM TO
TYPE OF WORK (check):	Top soil	0 2
Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐	White clay	2 11
f abandonment, describe material and procedure in Item 11.	Brown silt	11 20
	Blue_silt	20 38
(4) PROPOSED USE (check): (5) TYPE OF WELL:	Blue clay & silt mixed	3 <b>8</b> 75
Omestic 🔁 Industrial □ Municipal □ Rotary □ Driven □ Cable 🔁 Jetted □	Brown sand	75 78
tion T Test Well Other Dug Bored	Brown silt & clay mixed	78 <b>1</b> 01
Dug L. 2010	Fine sand & gravel .	101 106
6) CASING INSTALLED: Threaded  Welded  Welded	Blue clay	106 124
8" Diam. from 0 ft. to 170 ft. Gage 230.	Cement gravel	124 148
6 " Diam. from 158 ft. to 230 ft. Gage	Fine sand & silt	148 151
" Diam, from ft. to ft. Gage	. Cement gravel	151 165
	Blue clay	165 167
7) PERFORATIONS: Perforated? A Yes \( \subseteq \) No	Bravel imbedded in blue clay	167 192
Type of perforation used Star $\frac{1}{4}$ in, by $\frac{1}{2}$ in.	- Cement gravel	192 195
77/4 770	Blue clay imbedded in gravel	195 222
161 179	Fine sand & siltimpedded in grave.	. 222 <b>259</b>
perforations from 185 ft. to 230 ft.	1	
perforations fromft. toft		
perforations from ft. to ft		
(8) SCREENS: Well screen installed  Yes No		
Type		
Diam. Slot size Set from ft. to ft. to ft.	A (*** *************************	Sept. 7 19
CONSTRUCTION:  .ell gravel packed?   Yes No Size of gravel:	(13) PUMP:	
Gravel placed fromft. toft.  Was a surface seal provided?   Yes  No To what depth?ft.	Manufacturer's Name	
Material used in seal—  Did any strata contain unusable water?   Yes No	Well Driller's Statement:  This well was drilled under my jurisdiction	and this report
Type of water? Depth of strata  Method of sealing strata off	true to the best of my knowledge and belief.	-
(10) WATER LEVELS:	NAME John W. Beck Well Drilling (Person, firm, or corporation) (Type or print)  Address Rt. 3, Box 45, Canby, Ore.	
Static level 28 ft. below land surface Date 9/7/57  Artesian pressure lbs. per square inch Date	Driller's well number 394	
Log Accepted by:	[Signed] John W. Be. (Well Briller)	k.
[Signed] Jelly ate 9-8, 195		ot. 7 , 19 <sup>5</sup>