16-3615

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM, OREGON 97310 FNGINEESTATE OF OREGON within 30 days from the date of the contract of well completion.

State Well No.

within 30 days from the date of VREGON (Please type of well completion.	e or print) State Permit No.	
1) OWNER:	(11) WELL TESTS: Drawdown is amount water level is lowered below static level	
Vame Sennard Farschweiler	Was a pump test made? Yes No If yes, by whom?	
Address Rt 1 Boy 458	Yield: 650 gal./min. with / 9 ft. drawdown aft	ter 8 hrs.
My and lung to the	22 22	29
(2) LOCATION OF WELL:	22 23	**
	Bailer test gal./min. with ft. drawdown as	fter hrs.
County Marion Driller's well number	Artesian flow g.p.m. Date	· · · · · · · · · · · · · · · · · · ·
1/4 1/4 Section T. R. W.M.	Temperature of water 57 Was a chemical analysis made?	Yes X No
Bearing and distance from section or subdivision corner	(12) WELL LOG: Diameter of well below casing	***************************************
Sec 15-16, 7501124	Depth drilled /40 ft. Depth of completed well	140 ft.
The second secon		
The second secon	Formation: Describe by color, character, size of material and show thickness of aquifiers and the kind and nature of the m stratum penetrated, with at least one entry for each change	aterial in each
The state of the s	distant periodical activities and section of the control of the co	
(a) MADE OF MODIC (AL-AL).	MATERIAL FRO	
(3) TYPE OF WORK (check):	Top soil	5 2
Well Deepening Reconditioning Abandon	0	
r wandonment, describe material and procedure in Item 12.	Brown Clay 2	23
(4) PROPOSED USE (check): (5) TYPE OF WELL:	J	
Domestic Industrial Municipal Rotary Driven	- Office Clay 2.	5-76
Cable M Jetted L		
[rrigation ☐ Test Well ☐ Other ☐ Dug ☐ Bored ☐	Trine Sand 76	6 90
(6) CASING INSTALLED: Threaded Welded	100	
12 " Diam. from +20 to 140 ft. Gage 4	- Blue Clay	0 75
ft. Gage		
"Diam. fromft. toft. Gage	Chark Sand 9	3-115
(7) PERFORATIONS: Perforated? Yes No	RO O	5-120
The state of	Delue Clary 11	5 120
7	Black Sand. 12	0 138
Size of perforations in. by in. (a) perforations from	- WKACH Sand	7.00
472 perforations from 100 ft. to 140 ft.	March & Land	
perforations fromft. toft.	and up 5 6" 1:	35 139
perforations fromft, toft.	- grand - j	
perforations from ft. to ft.		
(8) SCREENS: Well screen installed? Tyes X No		
Manufacturer's Name		
Model No.		
Dram. Slot size Set from ft. to ft.	Work started 4//25 19/6 Completed 57//3	3 166
Diam, Slot size Set from ft. to ft.	Date well drilling machine moved off of well	<u>/ 19 6 (</u>
(9) CONSTRUCTION:	(13) PUMP:	
Well seal—Material used in seal	Manufactural Name	
Depth of seal ft. Was a packer used?	Manufacturer's Name	***************************************
Diameter of well bore to bottom of seal 20 in.	Type: H.P.	
Were any loose strata cemented off? Tes No Depth	Water Well Contractor's Certification:	
Was a drive shoe used? 🗆 Yes 🕺 No	This well was drilled under my jurisdiction and	this report is
Was well gravel packed? X Yes No Size of gravel:	true to the best of my knowledge and belief.	11111 TOPOT V 10
Gravel placed fromft. 5ft. ft.	NAME Grand Drillan & Su	and:
Did any strata contain unusuable water? ☐ Yes 😿 No	(Person, firm or corporation) (Type of	THE PARKET
Type of water? depth of strata	Address 729 M main mewo	un
Method of sealing strata off	D. W. Law C. D.	J
(10) WATER LEVELS:	Drilling Machine Operator's License No.	- Compared the State of the Sta
- 11 c	[Signed] Wash Dalkfullow	se_
Static level 19 4 ft. below and surface Date 3/13/66	(Water Well Contractor)	~ /
Artesian pressure lbs per square inch Date	Contractor's License No Date	5 1966

(USE ADDITIONAL SHEETS IF NECESSARY)