WATER WELL REPORT STATE OF OREGON

RECEIVED

SEP 0 4 1981

SALEM, OREGON

M ARI 2562 State Wellino. 55/210-17
State Permit No. 7-4505

WATER RESOURCES DEPT Y

(1) OWNER:	(10) LOCATION OF WELL:
Name George Berger	County Marion Driller's well number
Address 4447 Marthaler Rd.	4 4 Section / 7 T. 55 R. 2 W W.M.
City Cervais - Woodburn State Or.	Tax Lot # Lot Blk Subdivision
(2) TYPE OF WORK (check):	Address at well location: Same
New Well ⊠ Deepening □ Reconditioning □ Abandon □	(11) WATER LEVEL: Completed well.
If abandonment, describe material and procedure in Item 12.	Depth at which water was first found 86 ft.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Static level 34 ft. below land surface. Date 8/28-8
Rotary Air 🏋 Driven 🗆 Domestic 🛣 Industrial 🗆 Municipal 🗆 Rotary Mud 🗆 Dug 🗇 Irrigation 🗗 Test Well 🖂 Other	Artesian pressure lbs. per square inch. Date
Rotary Mud	(12) WELL LOG: Diameter of well below casing 6
ACING INCOMITED.	Depth drilled 108 ft. Depth of completed well 108 ft.
(5)—CASING INSTALLED: Steel IX Plastic III Threaded III Welded IX	Formation: Describe color, texture, grain size and structure of materials; and show
6 "Diam from +1 ft to 108 ft Gauge .250	thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level
ft. toft. Gauge	and indicate principal water-bearing strata.
LINER INSTALLED: no	MATERIAL From To SWL
"Diam from ft. to ft. Gauge	Soil med brn 0 1
	Clay med brn 1 25
(6) PERFORATIONS: Perforated? □ Yes ☒ No Type of perforator used	Clay sandy brn 25 43
Size of perforations in, by in.	Clay med blue 43 58
perforations fromft. toft.	Sand med brn, gray 58 63
perforations from ft. to ft.	Sand med blk 63 78
perforations from	Clay sticky blue 78 86
	Sand med blk 86 97
(7) SCREENS: Well screen installed? Yes No	Sand & gravel med gray 97 108
Manufacturer's Name Type	
Diam. Slot Size Set from ft. to ft.	Siptem will Not except T in app #
Diam. Slot Size Set from ft. to ft.	Sixtem will
Drawdown is amount water level is lowered	by except "
(8) WELL TESTS: below static level	Met - start -
Was a pump test made? ☐ Yes 🕅 No If yes, by whom?	two off
y gal./min. with ft. drawdown after hrs.	
" " "	
Air test 75 gal/min. With drill stem at 108 _{ft} . 1 hrs.	
Bailer test gal./min. with ft. drawdown after hrs.	
Artesian flow g.p.m.	
Perature of water Depth artesian flow encountered ft.	Work started 8/28 1981 Completed 8/28 1981
(9) CONSTRUCTION: Special standards: Yes \(\text{No } \text{M} \)	Date well drilling machine moved off of well $8/28$ 19 81
Well seal—Material used	Drilling Machine Operator's Certification:
	This well was constructed under my direct supervision. Materials used
Diameter of well bore to bottom of seal	and information reported above are true to my best knowledge and belief. [Signed] Dun Dun Date 8/31, 19.81
Number of sacks of cement used in well seal 14 sacks	Grilling Machine Operator)
How was cement grout placed? Press	Drilling Machine Operator's License No
Thow was cement group placed:	Water Well Contractor's Certification:
	This well was drilled under my jurisdiction and this report is true to
Was pump installed?	the best of my knowledge and belief.
Was a drive shoe used? Yes No Pluss Size: location ft.	Name West Coast Drilling Co. Inc. (Type or print)
Did any strata contain unusable water? Tyes No	Address 220/Academy St. Mt. Angel, Or.
Type of Water? depth of strata	Estado (Marles & X Trado):
Method of sealing strata off	[Signed] (Water Well Contractor)
Was well gravel packed? ☐ Yes ☐ No ☐ Size of gravel:	Contractor's License No. 519 Date 8/31 , 19.81
Gravel placed from ft. to ft.	