NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print) (Do not write above this line)

State Permit No.

(1) OWNER:	(10) LOCATION OF WELL:
Name Tare Vieta or	CountyMarion Driller's well number 2297
Address 4308 Marthalar Rd. N.E.	% % Section 18 T. 5S R. 2W W.M.
Woodburn, Oregon 97071	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well ∑ Deepening □ Reconditioning □ Abandon □	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL. Completed well
	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 61 ft.
Rotary N Driven Domestic N Industrial Municipal Domestic N	Static level 17 ft. below land surface. Date 5/16/80
Bored Irrigation Test Well Other	Artesian pressure lbs. per square inch. Date
(5) CASING INSTALLED: Threaded ☐ Welded 反 6 " Diam. from top ft. to 119 ft. Gage .250 ———————————————————————————————————	(12) WELL LOG: Diameter of well below casing Depth drilled 119 ft. Depth of completed well 119 ft. Formation: Describe color, texture, grain size and structure of materials;
" Diam. fromft. toft. Gage	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
(6) PERFORATIONS: Perforated? Yes No.	MATERIAL From To SWL
Type of perforator used	
Size of perforations in. by in.	
perforations from ft. to ft.	BLOWII CLAY
perforations from ft. to ft.	Dide Glay
perforations from ft. to ft.	Diack balle
(7) SCREENS: Well screen installed? Yes No	Didok Odilo diio Dia Dia
• •	Blue Clay 78 91 Black Sand 91 96
Manufacturer's Name	Black Sandy Gravel 96 101
Diam. Slot size Set from ft. to ft.	Blue Clay 101 104
Diam. Slot size Set from ft. to ft.	Black Sand 104 110
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Black Sand and Gravel 110 119
s a pump test made? Yes X No If yes, by whom?	
Yield: gal./min. with ft. drawdown after hrs. Airrtest 100+ GPM for a period of 1 hour "	RECEIVED
" " " "	JUN 2 1980
iler test gal./min. with ft. drawdown after hrs.	WATER RESOURCES DELT
rtesian flow g.p.m.	Work started 5/16/80 19 Completed 5/16/80 19
Temperature of water Depth artesian flow encountered ft.	Work started 5/16/80 19 Completed 5/16/80 19
(9) CONSTRUCTION:	Date well drilling machine moved off of well 5/16/80 19
Well seal—Material used Portland Cement Well sealed from land surface to 20 ft. Diameter of well bore to bottom of seal 10 in. Diameter of well bore below seal 6 in. Number of seals of sevent used in red seal 7 sacks	Drilling Machine Operator's Certification: This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief. [Signed] Drilling Machine Operator) Drilling Machine Operator: Drilling Machine Operator: 752
How was cement grout placed? pumped in thru conductor	Drilling Machine Operator's License No
pipe	Water Well Contractor's Certification:
	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used? Yes No Plus Size: location ft.	
Did any strata contain unusable water? TYes 1 No	Name Willamette DrillingCo. (Type or print)
Type of water? deptiof strata	Address 7365 O'Neil Rd. NE. Salem, Oregon 97303
Method of sealing strata off	[Signed] Dallon Lorais
Was well gravel packed? ☐ Yes ▼No Size of gravel:	(Water Well Contractor)
Gravel placed fromtoft.	Contractor's License No.561 Date 5/16/80 , 19
Gravel placed from	