1 RECEILE	D#10-10 10	11		
WATER WELL REPORT DE 00 4 1980	M State Well No	45/10	4-3	ca
STATE OF OREGON	Interment &	- /		
WATER RESOURCES	DEPT — Pan State Permit No.			
SALEM. OREGON	1 1/1/W# 1/0			
STATE OF OREGON WATER RESOURCES SALEM. OREGON				
(1) OWNER:	(10) LOCATION OF WELL:			
Name NICHOLAS DUBENKO	County CLACKAMAS Driller's well			
Address 13092 ARNDT RO		R. 100		W.M.
City AURORA State OR 97002	Tax Lot # Lot Blk		odivision	
(2) TYPE OF WORK (check):	Address at well location: 13092 ARNOT R	.0		
New Well		33		•
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w			_
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	86	5.4	ft.
		land surface er square ir		
Rotary Mud Dug				,
Cable Bored Thermal: Withdrawal Reinjection	(12) WELL LOG: Diameter of well below ft. Depth of	_		<u> - الاس</u>
CASING INSTALLED: Steel Plastic	Depth drilled 193 ft. Depth of Formation: Describe color, texture, grain size and str			
Threaded Welded Welded Threaded Grant Gauge Co. 250	thickness and nature of each stratum and aquifer pen-	etrated, wit	:h at leas	t one entry
Diam rous	for each change of formation. Report each change in and indicate principal water-bearing strata.	position of	Static W	ater Level
"Diam. from	• •	From	To	SWL
LINER INSTALLED:	MATERIAL	e e	7	
"Diam. from ft. to ft. Gauge	CIAY BROWN	1	21	
(6) PERFORATIONS: Perforated? Yes No	CLAY BROWD CLAY BLUE SILTY	27	75	
Type of perforator used STAR	CEMENT GRAVEL GREY	75	84	
Size of perforations //2 in. by 18 in.	Sans	86	87	40
\$20 perforations from 161 ft. to 187 ft.	CLAY SILTY GREY	87	92	
perforations from	CLAY BROWN	92	102	
perforations from ft. to ft.	SAMO BROWN FINE	102	144	
(7) SCREENS: Well screen installed? Yes No	CLAY BROWN	144	146	
Manufacturer's Name	CLAY GREY	146	162	
Type	CEMPUT GRAVEL	162	163	40
Diam. Slot Size Set from ft. to ft.	SAND & GRAVEL BROWN	163	193	70
Diam. Slot Size Set from ft. to ft. Drawdown is amount water level is lowered	CLAY SICTY BROWN	187	• • •	
WELL TESTS: below static level				
Was a pump test made? Yes \(\sum \) No If yes, by whom?				
d: 77.5 gal/min. with 97 ft. drawdown after 2 hrs.				
" 400 " 117 vext Lay 2 "				
Air test gal./min. with drill stem at ft. hrs.				<u> </u>
r test gal./min. with ft. drawdown after hrs.				<u> </u>
sian flow g.p.m.				
mperature of water Depth artesian flow encountered ft.		eted No	118	19 <u>19</u> متى 19
(9) CONSTRUCTION: Special standards: Yes 🗆 No	Date well drilling machine moved off of well	Nov		19
Well seal-Material used Cement	Drilling Machine Operator's Certification:			
Well sealed from land surface to 2. 4	This well was constructed under my direct and information reported above are true to my	t supervisi z best kno	ion. Mat wledge a	eriais used and belief.
Diameter of well bore to bottom of seal in.		Dat	e//-//	با 19.80.
Diameter of well bore below seal	(Drilling Machine Operator)	20		
How was cement grout placed?	Drilling Machine Operator's License No. 1.25			
How was cement grout placed:	Water Well Contractor's Certification:			
	This well was drilled under my jurisdicti	ion and th	is repor	t is true to
Was pump installed? Type HP Depth ft.	the best of my knowledge and solief.	r.	,	1
Was a drive shoe used? Yes No Plugs Size: location ft.	(Person, firm or corporation)	. 0.	W.	Graff (7
Did any strata contain unusable water? Yes Tho	Address 10309 St. Changes Gall	T. KN.		T. Con
Type of Water? depth of strata	[Signed] Kicker & Deck	<u>پ</u>		
Method of sealing strata off	(Water Well Cont		8	100
Was well gravel packed? ☐ Yes ☐ Yes Size of gravel:	Contractor's License No. 7.4.3Date	.T. T		, 134.9%.
Gravel placed from	WATER RESOURCES DEPARTMENT,			SP*12658-690